

VIEW ON MATING SIDE

C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C	C
A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø  
ø

A = 32 CONTACTS L=2,8

C = 32 CONTACTS L=2,8

S = 64 TOTAL NUMBER OF CONTACTS

Marking	Standard
Performance level	G2/0 = Contact area level2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85052-0001 sht.1
Technical Data	PS-85052-0001

C	G2/0	c1-32
A	G2/0	a1-32
Contact symbol	Perform. level	Contact position number

first release see ECN No. 2249	REVISIONS	FOR PREVIOUS REVISIONS SEE MRI LIST
UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ±2° INCH METRIC 3 PLACE ± . ± 2 PLACE ± . ± 1 PLACE ± . ± DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS DESIGN DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN. EQUIVALENT DIMENSION <input type="checkbox"/> MM <input type="checkbox"/> IN. IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY	DRWG BY <b>KN</b> CHK'D BY <b>TB</b> APP'D BY	SIGN SCALE
CAD/CAM PROJECT NAME S8505200 S01 THIS DRAWING CONTAINS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		
REVISE ONLY ON CAD SYSTEM		
SH. REV.		SHEET NO. DATE 1 OF 1 96/09/17
TITLE 96 pos. female connector acc. DIN 41612 style R contacts arrangement		
PART NO. DWG NO. 85052-0000 SDA-85052-0000		
LTR A		