




(1)









| N | 0 | ΓЕ | S: |
|---|---|----|----|
|   |   |    |    |

(IF PRESENT)

| MATERIAL:              |  |
|------------------------|--|
| HOUSING:               |  |
| SHELL:                 |  |
| CONTACT:               |  |
|                        |  |
| OPERATING TEMPERATURE: |  |
|                        |  |

**POWER/CO-AX CONTACT RATING:** 40A (CURRENT)

SIGNAL CONTACT CURRENT RATING: 5A PER CONTACT SIGNAL CONTACT RESISTANCE:  $10m\Omega$  MAX.

**INSULATOR RESISTANCE:** DIELECTRIC WITHSTANDING VOLTAGE:



THERMOPLASTIC POLYESTER, UL94V-0

COPPER ALLOY, GOLD FLASH PLATED


STEEL, NICKEL PLATED

-55°C ~ 125°C

5000MΩ min.

1000V AC rms

|                                      | SW REFERENCE NO.: 630 COMBO ASSEMBLY  |                                 |            |       |
|--------------------------------------|---|---------------------------------|------------|-------|
| COMBINATION                          | DRAWN: C.B  | DATE: JAN. 01/20                | 19         |       |
|                                      |   | CHECKED:                        | DATE:      |       |
| EDAC INC                             | THESE DRAWINGS AND SPECIFICATIONS<br>ARE THE PROPERTY OF EDAC INC.,AND  | SCALE: (IN C.A.D. 1:1)          | SHEET 1 OF | 2     |
| TORONTO, ONTARIO<br>CANADA           | SHALL NOT BE REPRODUCED, OR COPIED<br>OR USED AS THE BASIS FOR THE<br>MANUFACTURE OR SALE OF APPARATUS<br>WITHOUT WRITTEN PERMISSION. | DRAWING NUMBER: 630-2WK2240-4NB |            | ISSUE |
| YOUR CONNECTION TO QUALITY & SERVICE |   | PART NUMBER: 630-2WK            | 2240-4NB   | 1     |





THIS SERIES FULLY CONFORMS TO THE EUROPEAN UNION DIRECTIVES 2011/65/EU FOR RoHS COMPLIANCY.

