



ESD-R-512936H-NC23

Aliases (UECESDN0512903)

KEMET, ESD-R-NC, EMI Cores, Noise Suppression





Click here for the 3D model.

Dimensions		
D	51mm MAX	
D2	29.5mm +/-1mm	
Т	36mm MAX	

Packaging Specifications		
Packaging	Tray, Box	
Packaging Quantity	60	
Component Weight	145 g	

General Information		
Series	ESD-R-NC	
Style	Round - Toroidal	
Cable Type	Round Cable	
Description	EMI Core Solid, Large-Size Ring Type, For Round Cables	
Features	Low and High Frequency Range, Flame Retardancy	
RoHS	Yes	
SCIP Number	d5c28613-591c-4483-83c1-5d29064c1b21	
Qualifications	UL94V-0	
Case Color	Black with yellow tape	
Materials	Nanocrystal	

Specifications	
Temperature Range	-40/+120°C
Effective Frequency	10 MHz (AM Band Range) or 300 MHz (FM Band Range)

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.