


- Chassis mount with screw terminal block
- EN 50155 approval for railway applications
- Optional DIN-rail mounting kit
- Ultra wide 4:1 input voltage range
- Full load operation up to +60°C with convection cooling
- Undervoltage lockout
- Reverse input voltage protection
- Input protection filter
- 3-year product warranty



The TEP 75WICMF Series is a family of isolated high performance DC/DC converter modules with ultra-wide 4:1 input voltage ranges. They come in chassis mount version with screw terminal block. These converters are suitable for a wide range of applications, but the product is designed particularly also for industrial applications where often no PCB mounting is possible but the module has to be mounted on a chassis. Four threaded M3 inserts in the module makes chassis mount or attachment of a heatsink for optimal thermal management very simple. For easy connection there is also a unique adaptor available with screw terminals. A very high efficiency allows an operating temperature up to +60°C with natural convection cooling without power derating. Further features include output voltage trim, Remote On/Off and under voltage lockout. The very wide input voltage range and reverse input voltage protection make these converters also an interesting solution for battery operated systems.

Models				
Order Code	Input Voltage Range	Output Voltage nom. (adjustable)	Output Current max.	Efficiency typ.
TEP 75-2411WI-CMF	9 - 36 VDC (24 VDC nom.)	5 VDC (4.0 - 5.5 VDC)	15'000 mA	88 %
TEP 75-2412WI-CMF		12 VDC (9.6 - 13.2 VDC)	6'300 mA	88 %
TEP 75-2413WI-CMF		15 VDC (12.0 - 16.5 VDC)	5'000 mA	88 %
TEP 75-2415WI-CMF		24 VDC (19.2 - 26.4 VDC)	3'200 mA	87 %
TEP 75-2416WI-CMF		28 VDC (22.4 - 30.8 VDC)	2'700 mA	87 %
TEP 75-2418WI-CMF		48 VDC (38.4 - 52.8 VDC)	1'600 mA	87 %
TEP 75-4811WI-CMF	18 - 75 VDC (48 VDC nom.)	5 VDC (4.0 - 5.5 VDC)	15'000 mA	90 %
TEP 75-4812WI-CMF		12 VDC (9.6 - 13.2 VDC)	6'300 mA	90 %
TEP 75-4813WI-CMF		15 VDC (12.0 - 16.5 VDC)	5'000 mA	89 %
TEP 75-4815WI-CMF		24 VDC (19.2 - 26.4 VDC)	3'200 mA	88 %
TEP 75-4816WI-CMF		28 VDC (22.4 - 30.8 VDC)	2'700 mA	88 %
TEP 75-4818WI-CMF		48 VDC (38.4 - 52.8 VDC)	1'600 mA	87 %
TEP 75-7211WI-CMF	43 - 160 VDC (110 VDC nom.)	5 VDC (4.0 - 5.5 VDC)	15'000 mA	91 %
TEP 75-7212WI-CMF		12 VDC (9.6 - 13.2 VDC)	6'300 mA	91 %
TEP 75-7213WI-CMF		15 VDC (12.0 - 16.5 VDC)	5'000 mA	91 %
TEP 75-7215WI-CMF		24 VDC (19.2 - 26.4 VDC)	3'200 mA	90 %
TEP 75-7216WI-CMF		28 VDC (22.4 - 30.8 VDC)	2'700 mA	90 %
TEP 75-7218WI-CMF		48 VDC (38.4 - 52.8 VDC)	1'600 mA	90 %

Options	
<b>TEP-MK1</b>	- Optional DIN-Rail Mounting Kit: <a href="http://www.tracopower.com/products/tep-mk1.pdf">www.tracopower.com/products/tep-mk1.pdf</a>
<b>on demand</b> (backorder with MOQ non stocking item)	- Optional model with 3.3 VDC / 20'000 mA Output and 9 - 36 VDC Input - Optional model with 3.3 VDC / 20'000 mA Output and 18 - 75 VDC Input - Optional model with 3.3 VDC / 20'000 mA Output and 43 - 160 VDC Input - Optional models with inverse Remote On/Off function (passive = off)

### Input Specifications

Input Current	- At no load	110 Vin models: <b>10 mA typ.</b> 24 Vin models: <b>85 mA typ.</b> (3.3 Vout model) <b>120 mA typ.</b> (5 Vout model) <b>185 mA typ.</b> (12 Vout model) <b>185 mA typ.</b> (15 Vout model) <b>85 mA typ.</b> (24 Vout model) <b>85 mA typ.</b> (28 Vout model) <b>85 mA typ.</b> (48 Vout model) 48 Vin models: <b>60 mA typ.</b> (3.3 Vout model) <b>60 mA typ.</b> (5 Vout model) <b>90 mA typ.</b> (12 Vout model) <b>50 mA typ.</b> (15 Vout model) <b>50 mA typ.</b> (24 Vout model) <b>50 mA typ.</b> (28 Vout model) <b>50 mA typ.</b> (48 Vout model)
	- At full load	24 Vin models: <b>3'600 mA max.</b> 48 Vin models: <b>1'800 mA max.</b> 110 Vin models: <b>1'350 mA max.</b>
Surge Voltage	24 Vin models: <b>50 VDC max.</b> (1 s max.) 48 Vin models: <b>100 VDC max.</b> (1 s max.) 110 Vin models: <b>185 VDC max.</b> (1 s max.)	
Under Voltage Lockout	24 Vin models: <b>7.3 VDC min. / 7.7 VDC typ. / 8.1 VDC max.</b> 48 Vin models: <b>15.5 VDC min. / 16 VDC typ. / 16.3 VDC max.</b> 110 Vin models: <b>33 VDC min. / 34.5 VDC typ. / 36 VDC max.</b>	
Recommended Input Fuse	24 Vin models: <b>15'000 mA</b> (fast acting) 48 Vin models: <b>8'000 mA</b> (fast acting) 110 Vin models: <b>3'150 mA</b> (slow blow) (The need of an external fuse has to be assessed in the final application.)	
Reverse Voltage Protection	<b>Parallel diode</b> (external input fuse required)	
Input Filter	<b>Internal Pi-Type</b>	

### Output Specifications

Output Voltage Adjustment	-20% to +10% (By external trim resistor)
	See application note: <a href="http://www.tracopower.com/overview/tep75wicmf">www.tracopower.com/overview/tep75wicmf</a> Output power must not exceed rated power!
Voltage Set Accuracy	<b>±1% max.</b>
Regulation	- Input Variation (Vmin - Vmax) <b>0.1% max.</b> - Load Variation (0 - 100%) <b>0.1% max.</b>
Ripple and Noise (20 MHz Bandwidth)	3.3 Vout models: <b>100 mVp-p max.</b> (w/ 4.7 µF) 5 Vout models: <b>100 mVp-p max.</b> (w/ 4.7 µF) 12 Vout models: <b>125 mVp-p max.</b> (w/ 4.7 µF) 15 Vout models: <b>125 mVp-p max.</b> (w/ 4.7 µF) 24 Vout models: <b>250 mVp-p max.</b> (w/ 4.7 µF) 28 Vout models: <b>250 mVp-p max.</b> (w/ 4.7 µF) 48 Vout models: <b>350 mVp-p max.</b> (w/ 2.2 µF)

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Capacitive Load	3.3 Vout models: 60'600 µF max. 5 Vout models: 30'000 µF max. 12 Vout models: 5'250 µF max. 15 Vout models: 3'330 µF max. 24 Vout models: 1'330 µF max. 28 Vout models: 960 µF max. 48 Vout models: 330 µF max.
Minimum Load	Not required
Temperature Coefficient	±0.02 %/K max.
Start-up Time	60 ms typ. (110 Vin models) 25 ms typ. (other models)
Short Circuit Protection	Continuous, Automatic recovery
Output Current Limitation	150% typ. of Iout max. (110 Vin models) 110 - 140% (other models)
Overvoltage Protection	115 - 130% of Vout nom.
Transient Response - Response Time	200 µs typ. / 250 µs max. (25% Load Step)

### Safety Specifications

Safety Standards	- IT / Multimedia Equipment	EN 60950-1 EN 62368-1 IEC 60950-1 IEC 62368-1 UL 60950-1 UL 62368-1
	- Railway Applications	EN 50155
	- Certification Documents	<a href="http://www.tracopower.com/overview/tep75wicmf">www.tracopower.com/overview/tep75wicmf</a>

### EMC Specifications

EMI Emissions	- Conducted Emissions	EN 55011 class A (internal filter) EN 55011 class B (with external filter) EN 55032 class A (internal filter) EN 55032 class B (with external filter)
	- Radiated Emissions	EN 55011 class A (internal filter) EN 55011 class B (with external filter) EN 55032 class A (internal filter) EN 55032 class B (with external filter)
		External filter proposal: <a href="http://www.tracopower.com/overview/tep75wicmf">www.tracopower.com/overview/tep75wicmf</a>
EMS Immunity	- Electrostatic Discharge	EN 50155 (Railway Applications) EN 55024 (IT Equipment) EN 55035 (Multimedia)
	- RF Electromagnetic Field	Air: EN 61000-4-2, ±8 kV, perf. criteria A
	- EFT (Burst) / Surge	Contact: EN 61000-4-2, ±6 kV, perf. criteria A EN 61000-4-3, 20 V/m, perf. criteria A EN 61000-4-4, ±2 kV, perf. criteria A EN 61000-4-5, ±2 kV, perf. criteria A EN 61000-4-6, 10 Vrms, perf. criteria A
	- Conducted RF Disturbances	Continuous: EN 61000-4-8, 100 A/m, perf. criteria A
	- PF Magnetic Field	1 s: EN 61000-4-8, 1000 A/m, perf. criteria A

### General Specifications

Relative Humidity		95% max. (non condensing)
Temperature Ranges	- Operating Temperature	-40°C to +75°C
	- Case Temperature	+105°C max.
	- Storage Temperature	-40°C to +105°C

All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

Power Derating	- High Temperature	Depending on model See application note: <a href="http://www.tracopower.com/overview/tep75wicmf">www.tracopower.com/overview/tep75wicmf</a>
Over Temperature Protection Switch Off	- Protection Mode - Measurement Point	115°C typ. (Automatic recovery at 105°C typ.) Base-Plate
Cooling System		Natural convection (20 LFM)
Sense Function		10% max. of Vout nom.
Remote Control	- Voltage Controlled Remote  - Off Idle Input Current	On: 3.0 to 12 VDC or open circuit Off: 0 to 1.2 VDC or short circuit Refers to 'Remote' and '-Vin' Pin 3 mA typ. (Optional models with inverse logic available)
Altitude During Operation		2'000 m max.
Switching Frequency		270 - 330 kHz (PWM) 300 kHz typ. (PWM)
Insulation System		Reinforced Insulation (110 Vin models) Basic Insulation (other models)
Working Voltage (rated)		157 VAC (110 Vin models) 125 VAC (other input models)
Isolation Test Voltage	- Input to Output, 60 s  - Input to Case, 60 s  - Output to Case, 60 s	3'000 VAC (110 Vin models) 3'000 VDC (other models) 1'500 VAC (110 Vin models) 1'600 VDC (other models) 1'500 VAC (110 Vin models) 1'600 VDC (other models)
Isolation Resistance	- Input to Output, 500 VDC	1'000 MΩ min.
Isolation Capacitance	- Input to Output, 100 kHz, 1 V	2'500 pF max.
Reliability	- Calculated MTBF	336'000 h (MIL-HDBK-217F, ground benign)
Environment	- Vibration  - Mechanical Shock  - Thermal Shock	MIL-STD-810F EN 61373 MIL-STD-810F EN 61373 MIL-STD-810F EN 50155
Housing Material		Alu base-plate w. metal case (24 and 48 Vin models) Alu base-plate w. plastic case (110 Vin models)
Base Material		Non-conductive FR4 (UL 94 V-0 rated) (24 and 48 Vin models only)
Potting Material		Silicone (UL 94 V-0 rated)
Housing Type		Metal Case (24 and 48 Vin models) Plastic Case (110 Vin models)
Mounting Type		Chassis Mount
Connection Type		Screw Terminal
Weight		287 g
Thermal Impedance	- Case to Ambient	6.7 K/W typ.
Environmental Compliance	- REACH Declaration  - RoHS Declaration  - SCIP Reference Number - Flammability (EN 45545-2)	<a href="http://www.tracopower.com/info/reach-declaration.pdf">www.tracopower.com/info/reach-declaration.pdf</a> REACH SVHC list compliant REACH Annex XVII compliant <a href="http://www.tracopower.com/info/rohs-declaration.pdf">www.tracopower.com/info/rohs-declaration.pdf</a> Exemptions: 7a, 7c-I (RoHS exemptions refer to the component concentration only, not to the overall concentration in the product (O5A rule.)) 66bffc84-4b17-4968-857f-64909103fb65 <a href="http://www.tracopower.com/info/en45545-declaration.pdf">www.tracopower.com/info/en45545-declaration.pdf</a>


All specifications valid at nominal voltage, resistive full load and +25°C after warm-up time, unless otherwise stated.

### Supporting Documents

Overview Link (for additional Documents)

[www.tracopower.com/overview/tep75wicmf](http://www.tracopower.com/overview/tep75wicmf)

### Outline Dimensions



Pinout	
Pin	Function
1	-Vin (GND)
2	NC
3	Remote
4	+Vin (Vcc)
5	-Vout
6	-Sense*
7	Trim
8	+Sense*
9	+Vout

NC: Not connected

\*Sense line to be connected to the output either at the module or at the load under regard of polarity.

Dimensions in mm (inch)  
Tolerances  $x.x \pm 0.5$  ( $x.xx \pm 0.02$ )  
 $x.xx \pm 0.25$  ( $x.xxx \pm 0.01$ )

Screw 3:  
Type M4  
Head diameter 6.88 (0.271)  
Rated current: 15 A

The screw1 locked torque:  
MAX 11.2kgf-cm/1.10N-m

The screw2 locked torque:  
MAX 5.2kgf-cm/0.51N-m

The screw3 locked torque:  
MAX 12kgf-cm/1.18N-m