


ULTRA MICRO POWER CABLE



SERIES	NO. OF POSITIONS	PLATING OPTION	WIRE GAUGE	LATCH OPTION	LENGTH	PINOUT
UMPC = Ultra Micro PVC Cable	-02, -03, -04, -05, -06, -07, -08, -09, -10	-L = 10 μ" (0.25 μm) Gold on contact, Tin on tail	-16 = 16 AWG	(Latching required)	-"XX.X" = Assembled Length in Inches Single ended = (76.2 mm) 03.0" min. Double ended = (101.6 mm) 04.0" min. (2-4 positions) Double ended = (127.0 mm) 05.0" min. (5-10 positions)	(Leave blank for Single ended)
UMPCT = Ultra Micro Blue *Teflon® Cable		-S = 30 μ" (0.76 μm) Gold on contact, Tin on tail	-16C = Color Coded Cable (UMPC only)	-P = Plastic top latch		-1 = Pin 01 to Pin 01
		-T = Tin	-18 = 18 AWG	-M = Metal side latches		-2 = Pin 01 to Pin N
			-18C = Color Coded Cable (UMPC only)			

UMPCT PRELIMINARY

UMPC(T)

Board Mates:

UMPT

(Plastic (-P) or metal (-M) latch required)

SPECIFICATIONS

Insulator Material:

Black LCP

Contact Material:

Copper Alloy

Plating:


Sn or Au over 50 μ" (1.27 μm) Ni

Wire:

16 or 18 AWG

Voltage Rating:

300V PVC




UMPC-04-X-XX-M-XX.X SHOWN

UMPC/UMPT (TIN PLATING)


PINS	CURRENT RATING (PER CONTACT)
1	16.8 A
2	14.6 A
3	12.6 A
4	11.6 A
10	8.8 A

CABLE COLOR CODING

PIN	COLOR
1	BROWN
2	RED
3	ORANGE
4	YELLOW
5	GREEN
6	BLUE
7	VIOLET
8	GRAY
9	WHITE
10	BLACK



UMPC-03-X-XX-P-XX.X SHOWN



View complete specifications at: samtec.com?UMPC & samtec.com?UMPT

*DuPont™ Teflon® is a registered trademark of the E.I. du Pont de Nemours and Company or its affiliates.

Note: For wiring option information refer to drawings on web.

UMPC CABLE HOLDER (Required for use with IMPC)

SERIES	NUMBER OF POSITIONS	LEAD STYLE
IMPC	-02, -03, -04, -05, -06, -07, -08, -09, -10	01 = 16 AWG
		02 = 18 AWG

IMPC


NO. OF POSITIONS

-02, -03, -04, -05, -06, -07, -08, -09, -10

LATCH OPTION

-P
= Plastic top latch

-M
= Metal side latches



CC489

01

PLATING

-L
= 10 μ" (0.25 μm) Gold on contact, Tin on tail

-S
= 30 μ" (0.76 μm) Gold on contact, Tin on tail


-T
= Tin

PACKAGING

-R
= Contact, Full Reel

-M
= Contact, Mini Reel

-B
= Bubble Bag (35 Parts)



TOOLING

Hand Tool: CAT-HT-489-1618-13

Mini Applicator: CAT-MC-489-1618-XX-01

Note:

Some lengths, styles and options are non-standard, non-returnable.

View complete specifications at: samtec.com?IMPC & samtec.com?CC489