


C4BSYBX3470ZFMJ

C4BS, Film, Metallized Polypropylene, Power, 0.47 uF, 5%, 750 VAC, 3000 VDC, 70°C, Lead Spacing = 37 mm



Click here for the 3D model.

Dimensions	
L	57.5mm +1.2/-0.7mm
Н	45mm +0.3/-0.7mm
Т	30mm +0.5/-0.7mm
S	37mm +/-0.2mm
S1	31mm +/-0.2mm
S2	43mm +/-0.2mm
Р	21mm NOM

Packaging Specifications	
Packaging	Bulk, Bag
Packaging Quantity	24

General Information			
Series	C4BS		
Dielectric	Metallized Polypropylene		
Style	Radial		
Features	IGBT Circuit		
RoHS	Yes		
Lead	Flat Tabs		
AEC-Q200	No		
Component Weight	125 g		
Miscellaneous	KEMET Style F Tabs.		

Specifications			
Capacitance	0.47 uF		
Capacitance Tolerance	5%		
Voltage AC	750 VAC		
Voltage DC	3000 VDC		
Temperature Range	-40/+85°C		
Rated Temperature	70°C		
Max dV/dt	1280 V/us		
Resistance	7.5 mOhms (100kHz)		
Ripple Current	20 Amps (100kHz 70C), 602 Amps (Peak)		
Inductance	45 nH		

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.