

Specification Sheet

Part Number: 151-02802



Connector clip designed to meet USCAR EWCAP-005-7 clip slot specifications, assuring compliance.

Meets installation and extraction requirements of SAE/USCAR-2, for ease of insertion and reliable performance.

Offset design allows for clearance from obstructions and sheet metal contours.

Conn. Clip w/Offset M10 Thread Stud Mount, 28mm Offset, 7mm Conn Clip, PA66HIRHSUV, BK, 2000/ctn

Article Number 151-02802

Type CCM10SO28R

Color Black (BK)

Quantity Per carton

Product Description Connector Clips feature various attachment point configurations to accommodate the many connectors on the market. They are first mated with a connector on a wire harness or cable assembly, then secured to a surface using the integrated mount. With so many configurations available, attachment surfaces can be a hole, edge, stud or even another harness assembly.

Short Description Conn. Clip w/Offset M10 Thread Stud Mount, 28mm Offset, 7mm Conn Clip, PA66HIRHSUV, BK, 2000/ctn

Global Part Name	CCM10SO28R-PA66HIRHSUV-BK
Length L (Imperial)	1.53
Length L (Metric)	38.9
Offset Length (Imperial)	1.102
Offset Length (Metric)	28.0
Variant	M10 Threaded Stud 28 mm Offset
Height H (Imperial)	0.736
Height H (Metric)	18.7
Stud Diameter (Metric)	M10
Stud Diameter (Imperial)	0.3937
Material	Polyamide 6.6 high impact modified, heat and UV stabilized (PA66HIRHSUV)
Material Shortcut	PA66HIRHSUV
Operating Temperature	-40°F to +221°F (-40°C to +105°C)
Reach Compliant (Article 33)	No

ROHS Compliant Yes

Package Quantity (Imperial) 2000

Package Quantity (Metric) 2000