

## ATGBICS CWDM-SFP-2.5G-1470-80-C network transceiver module Fiber optic 2500 Mbit/s 1470 nm

Brand : ATGBICS

Product code: CWDM-SFP-2.5G-1470-80-C

Product name : CWDM-SFP-2.5G-1470-80-C

Cisco Compatible Transceiver, CWDM SFP 2.5G, 80km, SMF, LC, 1470nm

ATGBICS CWDM-SFP-2.5G-1470-80-C network transceiver module Fiber optic 2500 Mbit/s 1470 nm:

ATGBICS CWDM-SFP-2.5G-1470-80 2.5GBase CWDM supports a distance of up to 80km over single mode fibre (SMF) using a wavelength of 1470nm via an LC connector. Digital optical monitoring (DOM) support is also present enabling real-time monitoring of the parameters of the fibre optic transceiver. Our product is built to the exact specification of CiscoCWDM-SFP-2.5G-1470-80= and we proudly offer a compatibility guarantee and lifetime warranty. Our rigorously tested products record a unique traceable serial number and are fully compliant with all MSA Standards.





Performance		Features	
SFP transceiver type *Fiber opticMaximum data transfer rate *2500 Mbit/sInterface type *SFPSingle-mode fiber (SMF) supported✓Multi-mode fiber (MMF) supportedXFiber optic connectorLC	2500 Mbit/s	Brand compatibility	Cisco
		Power	
	Input voltage Maximum voltage Power consumption (typical)	3.3 V 3.5 V 1 W	
SFP transceiver standard Maximum transfer distance Wavelength Coarse Wavelength Division Multiplexing (CWDM) Ethernet interface type	anum transfer distance     80000 m       ength     1470 nm       e Wavelength Division     Image: CWDM)       lexing (CWDM)     25 Gigabit Ethernet	Operational conditions Maximum operating temperature Operating temperature (T-T) Storage temperature (T-T) Operating relative humidity (H-H) Storage relative humidity (H-H)	70 °C 0 - 70 °C -40 - 85 °C 0 - 95% 0 - 95%
Digital Diagnostics Monitoring (DDM)	4	Weight & dimensions	
Features Product colour Silver Housing material Metal	Width Depth Height Weight	13.4 mm 56.5 mm 8.5 mm 15 g	
Plug and Play Hot-swap	ot-swap 🗸 asy to install 🗸	Packaging data	
Easy to install Country of origin		Number of products included Package type	1 pc(s) Box
		Technical details	

Sustainability certificates

RoHS



Disclaimer. The information published here (the "Information") is based on sources that can be considered reliable, typically the manufacturer, but this Information is provided "AS IS" and without guarantee of correctness or completeness. The Information is only indicative and can be changed at any time without notification. No rights can be based on the Information. Suppliers or aggregators of this Information do not accept any liability with regard to the content of (web)pages and other documents, including its Information. The publisher of the Information can not be held liable for the content of 3rd party websites that are linking this Information or are linked to from this Information. You as the User of the Information are solely responsible for the choice and usage of this Information. You are not entitled to transfer, copy or otherwise multiply or distribute the Information. You are obliged to follow the directions of the copyright owner(s) with regard to the use of the Information. Exclusively Dutch law is applicable. With regard to price and stock data on the site, the publisher followed a number of starting points, which are not necessarily relevant for your private or business circumstances. Therefore, the price and stock data are only indicative and are subject to changes. You are personally responsible for the way you use and apply this information. As a user of the Information or sites or documents in which this Information is included, you will adhere to standard fair use including avoidance of spamming, ripping, intellectual-property violations, privacy violations, and any other illegal activity.