

PRIMARY: 1004220820 (F3201S-6.25-N) Use capacitance gauge and run FFT:	
1. SRL: VoP : 70%; Core Dia.: 0.008; Outer Dia.: 0.0205 2. Display SRL: X-Axis: 0-25 GHz; Y-Axis: -50 to 0 dB 3. Display Spectrograph: Y-Axis (SRL Freq. Range): 1-25 GHz; Value Range (Color Spectrum): -35 to -20 4. Flag if Spectrograph is showing solid color <-32 dB Engineering to determine if Wire Straighteners are needed.	
STRIP FORCE	>0.5 lbs., 3" Slug
PPK (Print OD & Concentricity SPC Summary for each spool)	>1.33 Ref.

HELICAL FOIL SHIELD: 1000680080	
LAY LENGTH (RH) / ANGLE	0.100" / 50 degrees
HEAT SEALED JACKET: HEAT SEALING required (Adhesive Side In) Print Legend (Drain Wire Side): MOLEX TEMP-FLEX(R) <LOCATION CODE: US or PHL or GDL> TWINMAX(TM) 32 AWG 1000680080 --- E61522 < UL CODE: -MPI for PHL, <blank> for US, -MDM for GDL> cRUus AWM 22046 I A/B 105C 30V FT1 VW-1 --- <TRACEABILITY> <TRACEABILITY> = Lot/Batch#, Mfg. Date (format: YYYYMMDD) Sequential Footage Marking	
TDR and VNA CHECK 1 start and end sample. Length = 6ft. 7in. (2m)	
LAY LENGTH (LH) / ANGLE	0.100" / 50 degrees

ELECTRICAL TDR & VNA CHECK 1 start and end sample per spool. Length = 6ft. 7in. (2m)	
--	--

LENGTHS REQUIRED	LENGTHS PER SPOOL	MIN. LENGTH	SPLICE CODE	SPOOL SIZE
Any	3	200'	N/A	12X7X5