


Magnet coil for contactor S3, 230 V AC, 50 / 60 Hz,



General technical data	
product brand name	SIRIUS
product designation	Magnet coil
Control circuit	
type of voltage of the control supply voltage	AC
control supply voltage frequency	<ul style="list-style-type: none"> <li>1 rated value 50 Hz</li> <li>2 rated value 60 Hz</li> </ul>
control supply voltage	<ul style="list-style-type: none"> <li>1 at AC                             <ul style="list-style-type: none"> <li>— at 50 Hz rated value 230 V</li> <li>— at 60 Hz rated value 230 V</li> </ul> </li> </ul>
operating range factor control supply voltage rated value of magnet coil at AC	<ul style="list-style-type: none"> <li>at 50 Hz 0.8 ... 1.1</li> <li>at 60 Hz 0.85 ... 1.1</li> </ul>

Certificates/ approvals			
General Product Approval	EMC	Declaration of Conformity	Marine / Shipping

[Confirmation](#)



Marine / Shipping	other
-------------------	-------



[Confirmation](#)

### Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<https://www.siemens.com/ic10>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3RT2944-5AL21>

Cax online generator

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3RT2944-5AL21>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3RT2944-5AL21>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)  
[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3RT2944-5AL21&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3RT2944-5AL21&lang=en)

last modified:

1/12/2021 