ASSOCIATION CONNECT	© Copyright 2005, IPC.	Material Composition Declaration © Copyright 2005. IPC, Bannockburn, Illinois. All rights reserved under both international and Pan-American copyright conventions.				This document is a declaration of the substances within the manufacturer listed item. Note: if the item is an assembly with low level parts, the declaration encompasses all lower level materials for which the manufacturer has engineering responsibility.										
752-21.1		IPC Web Site for Information on IPC-1752 Standard Form Type http://www.ipc.org/IPC-175x Distribute				* Declaration Class * Class 6 - RoHS Yes/No, Homogeneous Mater						als and Mf	g Info	rmation		
upplier Info	rmation															
Company name* Cor			Company un	Company unique ID			Unique ID Authority					Response Date*				
nsemi												2023-06-08				
Contact Name		Title - Contact			P	Phone - Contact*					Email - Contact*					
Product-Env-Ste	wards	Product Enviro Compliance			1	NA					Product-Env-Stewards@onsemi.com					
authorized Repro	esentative*	Title - Representative			P	Phone - Representative*				Email - Representative*						
Product-Env-Stewards			Product Enviro Compliance			1	NA				Product-Env-Stewards@onsemi.com					
Reque	ester Item Number	NCP715MX30TBG 50 mA Ultra-		tem Number Mfr Item Name			Effective Dat	Date Version Ma		Manufacturing Site		W	eight* UOM		Unit Type	
				50 mA Ultra-Lov Low Dropout Lir	ow Iq, Wide Input Voltage, inear Voltage Regulator		2023-06-08		N	MY1		3.64		1	mg	Each
<b>Ianufacturin</b>	g Proccess Information	1														
Termin	al Plating / Grid Array Material		Terminal Base Alloy		J-STD-020 MSL R	-020 MSL Rating		Peak Process Body Temperature		e Max Ti	1ax Time at Peak Temper		re N	Number of	Reflow Cyc	les
Precious metal (e.g. Ag,Au, NiPdAu) (no Sn)		u) (no	CU Alloy 1		1		260		С		30 seco		s <b>3</b>	3		
Comments																
vel 1 - maximun	n time at peak temperature (	during sol	dering is 10-3	30 seconds						·	·	·			·	
or more informa	ation regarding material con	position	please refer to	page 3												

RoHS Material Composition Declaration			Declaration Type *	Detail	led							
Directive 2015/863/EU amending RoHS Directive 2011/65/EU  RoHS Definition: Quantity limit of 0.01% by mass (100 PPM) in homogeneous material for Cadmium and quantity limit of 0.1% by mass (1000 PPM) in homogeneous material for: Lead (Pb), Mercury (Hg), Hexavalent Chromium (Cr6+), Polybrominated Biphenyls (PBB), Polybrominated Diphenyl Ethers (PBDE), and Bis(2-ethylhexyl) phthalate (DEHP), Benzyl-butyl phthalate (BBP), Dibutyl phthalate (DBP), Diisobutyl phthalate (DIBP).												
Please indicate whether any homogeneous material (as defined by the RoHS Directive, EU 2011/65/EU and implemented by the laws of the European Union member states) of the part identified on this form contains lead, mercury, cadmium, hexavalentchromium, polybrominated biphenyls and/or polybrominated diphenyl ethers (each a "RoHS restricted substance") in excess of the applicable quantity limit identified above. If a homogeneous material within the part contains a RoHS restricted substance inexcess of an applicable quantity limit, please indicate below which, if any, RoHS exemption you believe may apply. If the part is an assembly with lower level components, the declaration shall encompass all such components. Supplier certifies that it gathered the information it provides in this form using appropriate methods to ensure its accuracy and that such information is true and correct to the best of its knowledge and belief, as of the date that Supplier completes this form. Supplier acknowledges that Company will rely on this certification in determining the compliance of its products with European Union member state laws that implement the RoHS Directive. Company acknowledges that Supplier may have relied on informationprovided by others in completing this form, and that Supplier may not have independently verified such information. However, in situations where Supplier has not independently verified information provided by others, Supplier agrees that, at a minimum, its suppliers have provided certifications regarding their contributions to the part, and those certifications are at least as comprehensive as the certification in this paragraph. If the Company and the Supplier enter into a written agreement with respect to the identified part, the terms and conditions of that agreement, including any warranty rights and/or remedies of Supplier's Standard Terms and Conditions of Sale applicable to such part shall apply.												
RoHS Declaration * 1 - Item	(s) does not contain RoHS restricted substa	ances per the definition above	Supplier Ac	ceptance *	Accepted							
Exemption: If the declared item does not contain RoHS restricted substances per the definition above except for defined RoHS exemptions, then select the corresponding response in the RoHS Declaration above and choose all applicable exemptions.												
Exemption List Version	EL-2011/534/EU											
Declaration Signature												
Instructional Complete all of the required	fields on all neggs of this form. Calcut th		a duan dawn. This will display the signature on	a Digitally sign	the declaration (if recurined by the							
Instructions: Complete all of the required Requester) and click on Submit Form to			e drop-down. This will display the signature ar	ea. Digitally sign	the declaration (if required by the							

## **Homogeneous Material Composition Declaration for Electronic Products**

SubItem Instructions: The presence of any JIG Level A or B substances must be declared. [1] indicate the subpart in which the substance is located, [2] provide a description of the homogeneous material [3], enter the weight of the homogeneous material.

Substance Instructions: [A] select the Level (JIG A, JIG B, Requester or Supplier) [B] select the substance category (JIG or Requester) or enter a value (Supplier). [C] select the substance (JIG) or enter the substance and CAS (Other). [D] select a RoHS exemption, if applicable [E] enter the weight of the substance or the PPM concentration [F] Optionally enter the positive (+) and negative (-) tolerance in percent (Note: percent tolerance values are expected to cover a 3 sigma range of distribution unless otherwise noted).

Homogeneous Material	Weight	Unit of Measure	Level	Substance	CAS	Exempt	Weight	Unit of Measure
Die	0.25	mg	Supplier	Silicon (Si)	7440-21-3		0.25	mg
Die Attach	0.18	mg	Supplier	Epoxized Condensate Of Para- Hydrobenzaldehyde And Alkyl Phenol	129915-35-1		0.108	mg
			Supplier	Aluminum Trioxide (Al2O3)	1344-28-1		0.072	mg
Lead Frame	1.9	mg	Supplier	Tin (Sn)	7440-31-5		0.0047	mg
			Supplier	Zinc (Zn)	7440-66-6		0.0042	mg
			Supplier	Chromium (Cr)	7440-47-3		0.0047	mg
			Supplier	Copper (Cu)	7440-50-8		1.8863	mg
Mold Compound-Black	1.27	mg		Epoxy resin	proprietary data		0.0889	mg
			Supplier	Phenolic Resin	Proprietary Data		0.0889	mg
			Supplier	Silica Amorphous (SiO2)	7631-86-9		0.1905	mg
			Supplier	Carbon Black (C)	1333-86-4		0.0063	mg
			Supplier	Fused Silica (SiO2)	60676-86-0		0.8953	mg
Plating	0.03	mg	Supplier	Palladium (Pd)	7440-05-3		0.0007	mg
			В	Nickel (Ni)	7440-02-0		0.0264	mg
			Supplier	Gold (Au)	7440-57-5		0.0028	mg
Wire Bond - Au	0.01	mg	Supplier	Gold (Au)	7440-57-5		0.01	mg