



REVISIONS									
REV	ECO	DESCRIPTION	DATE	BY	APPR				
A1		FIRST RELEASED	APR-10-2020	BLINK	TOMMY				









TELECOM 4mm CONNECTOR, PLUG INSULATOR

PL000729

NOTES: (UNLESS OTHERWISE SPECIFIED)

1. MATERIAL:

SHELL: THERMOPLASTIC, UL94 V-0.

2. SPECIFICATIONS:

2.1, OPERATING TEMPERATURE: -40~125°C.

2.2, RoHS COMPLIANT.

3. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

QUANTITY	PART N	NUMBER		DESCRIPTION					ITEM		
		N	ЛAТ	ERI	٩LS	S LI	ST				
UNLESS OTHER	WISE SPECIFIED		ATURES	DATE	Amphenol						
2) Tolerances are a 1 PL DEC ±0.30	as follows: Fractions ±1/64 Angles ±1°	DRAWN:	BLINK	APR-10-2020		Amplication				<u> </u>	
2 PL DEC ±0.15 3 PL DEC ±0.08		CHECKED:	ORION	APR-13-2020				com			
3) Note reference	= X	ENGINEER:			44724 Morley Drive Clinton Township, MI 48036						
MATERIAL SPECIFICA	TIONS:	APPROVAL:	TOMMY	APR-15-2020							
		CUSTOMER:			4MM, CONTACT RETAINER CLIP						
			THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY. DESIGN FEATURES,			FOR USE WITH PL000728, PRM SERIES™					
PROCESS SPECIFICATIONS:					B	ТҮРЕ	DWG NO:	PL0007	29	F	A1
NEXT ASS'Y:		MANUFACTURING VARIATI		NS.	SCALE: N	ONE			SHEET	1 of	1