



Click [here](#) for the 3D model.

Dimensions

| | |
|-----------|---|
| Chip Size | 1210 |
| L | 3.07mm +/-0.38mm (0.121 in +/-0.015 in) |
| W | 2.56mm +/-0.38mm (0.101 in +/-0.015 in) |
| T | 1.6mm MAX (0.063 in MAX) |
| B | 0.51mm +/-0.25mm (0.02 in +/-0.01 in) |

Packaging Specifications

| | |
|-----------|-----------|
| Packaging | Bulk, Bag |
|-----------|-----------|

General Information

| | |
|-------------------------|--|
| Series | GR900 SMD Space |
| Style | SMD Chip |
| RoHS | No |
| Prop 65 | ⚠ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov |
| SCIP Number | 2a1e1a41-ed35-45dd-8d0d-907fc06efdab |
| Termination | Lead (SnPb) |
| Failure Rate | N/A |
| Testing and Reliability | GR900 CSAM A |
| AEC-Q200 | No |
| Shelf Life | 78 Weeks |
| MSL | 1 |

Specifications

| | |
|-------------------------|------------|
| Capacitance | 0.027 uF |
| Capacitance Tolerance | 5% |
| Voltage DC | 100 VDC |
| Temperature Range | -55/+125°C |
| Temperature Coefficient | BX |