



Click [here](#) for the 3D model.

### Dimensions

|    |                  |
|----|------------------|
| L  | 18mm +0.3/-0.5mm |
| H  | 10mm +0.1/-0.5mm |
| T  | 4mm +0.2/-0.5mm  |
| S  | 15mm +/-0.4mm    |
| LL | 25mm +2/-1mm     |
| F  | 0.8mm +/-0.05mm  |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Bulk, Bag |
| Packaging Quantity | 1500      |

### General Information

|                  |                                 |
|------------------|---------------------------------|
| Series           | R76                             |
| Dielectric       | Double Metallized Polypropylene |
| Style            | Radial                          |
| Features         | Automotive Grade, Pulse         |
| RoHS             | Yes                             |
| Lead             | Wire Leads                      |
| Qualifications   | AEC-Q200                        |
| AEC-Q200         | Yes                             |
| Component Weight | 1.125 g                         |

### Specifications

|                       |                                       |
|-----------------------|---------------------------------------|
| Capacitance           | 1000 pF                               |
| Capacitance Tolerance | 5%                                    |
| Voltage AC            | 700 VAC                               |
| Voltage DC            | 2000 VDC                              |
| Temperature Range     | -55/+110°C                            |
| Rated Temperature     | 85°C                                  |
| Dissipation Factor    | 0.03% 1kHz, 0.04% 10kHz, 0.1% 100kHz  |
| Insulation Resistance | 100 GOhms                             |
| Max dV/dt             | 9500 V/us                             |
| Resistance            | 636.62 mOhms (100kHz)                 |
| Ripple Current        | 0.4 Amps (100kHz 85C), 10 Amps (Peak) |
| Inductance            | 10 nH                                 |