

Relay module, Screw connection, 1 CO contact, power relay, Soldered, Input voltage: 48 VAC

### Business data

Article number	5801.2
Article name	RML/1W/24V AC
GTIN (EAN)	4044211069858
Packaging unit	1
Quantity unit	PC
Weight per piece (not including packaging)	47.8 g
Weight per piece (including packaging)	71.4 g
Unit of weight	G
Customs number	85364900
Country of origin	NL
Product description	Relay module

### Technical data

#### Dimensions

Length	87 mm
Width	24 mm
Height	68 mm

#### Ratings

Overvoltage category	III
Contamination degree	2

#### Connection data

Connection principle	Screw connection
Wire cross-section single core (rigid), min.	0.08 mm <sup>2</sup>
Wire cross-section single-core (rigid), max.	4 mm <sup>2</sup>
Wire cross-section stranded, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded, max.	2.5 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, min.	0.2 mm <sup>2</sup>
Wire cross-section stranded with wire-end ferrules, max.	2.5 mm <sup>2</sup>
Stripping length	7 mm
Torque	0.6 Nm

#### Input data

Input voltage	24 VAC/DC
Number of channels	1
Power consumption	0.5 W
reverse-polarity protection diode	1

#### Output data

Switching voltage / switching voltage max.	250 / 250 VAC
Continuous current max. / Inrush current max.	16 / 25 A
Contact configuration	1 CO contact
Switching capacity, max.	4000 VA
Electrical lifespan (AC1)	2x10 <sup>7</sup>
Mechanical lifespan	10x10 <sup>7</sup>

#### Materials

Contact material	AgNi 90/10
Working temperature, min.	-20 °C
Working temperature, max.	55 °C

---

### Technical data

---

#### Further technical data

Protection class	IP20
Insulation voltage coil/contact	4 kV
Status display red	✓
Response/release time	15 / 8 ms

#### Environmental Product Compliance

REACH Conform	yes
REACH Reference date	2022-01-07
REACH Candidate Substance Note	No
RoHS Conform	yes

### Approvals

---

#### Standards and regulations

---


CE compliant	yes
Standards / specifications	DIN VDE 0110 / EN 50178

---

---

### Media

---



---

### Accessories

---