

[Home](#) > [5642210132F](#)

Search For  Part Number

Part Number: **5642210132F**

#### General Description


Series	564
Configuration	3 mm Lens
Description	3 mm Red/Yellow/Green Backlighting Tri -Level CBI Non -Diffused
Package Options	Bulk Packaging
Sizes	3mm
Lamp Type	Tri -Level Housing
Viewing	Right Angle
Polarity	Cathode Right
Lens Style	Tinted, Non -Diffused
Viewing Angle	60
LED Centerline	2.54mm

#### Absolute Maximum Ratings (Ta = 25Å °)

Reverse Current	100 @ Vr = 5V
Solder Temperature	260 for 5 secs
Operating Temperature	-55 to +100
Storage Temperature	-55 to +100

#### Operating Characteristics

	LED Position: 1	LED Position: 2	LED Position: 3
Color	Red	Yellow	Green
LED Type	Standard Efficiency	Standard Efficiency	Standard Efficiency
Peak Wave Length	585	565	585
Luminous Intensity Min	10	32	10
Luminous Intensity Typical		50	
Forward Voltage Typical	2.1	2.1	2.1
Forward Voltage Max	2.8	2.8	2.8
Power Dissipation Max	100mW	60mW	100mW



5642210132F

[check stock](#)



[This is a RoHS Compliant Product. To learn more click here.](#)