



Note: '()' correspond to the letters used in the product bulletin

Click [here](#) for the 3D model.

### Dimensions

|           |                 |
|-----------|-----------------|
| Chip Size | 5045            |
| L         | 12.7mm +/-0.2mm |
| W         | 11.5mm +/-0.2mm |
| T         | 6.5mm +/-0.2mm  |
| F         | 0.5mm NOM       |

### Packaging Specifications

|                    |     |
|--------------------|-----|
| Packaging          | T&R |
| Packaging Quantity | 600 |

### General Information

|                |                              |
|----------------|------------------------------|
| Series         | F161                         |
| Dielectric     | Metallized Polyester Stacked |
| Style          | SMD Chip                     |
| Features       | Automotive Grade             |
| RoHS           | Yes                          |
| Qualifications | AEC-Q200                     |
| AEC-Q200       | Yes                          |
| Shelf Life     | 104 Weeks                    |
| MSL            | 3                            |

### Specifications

|                       |                       |
|-----------------------|-----------------------|
| Capacitance           | 3.3 uF                |
| Capacitance Tolerance | 5%                    |
| Voltage AC            | 40 VAC                |
| Voltage DC            | 63 VDC                |
| Temperature Range     | -55/+125°C            |
| Rated Temperature     | 85°C                  |
| Dissipation Factor    | 0.8% 1kHz, 1.5% 10kHz |
| Insulation Resistance | 121.21 MOhms          |
| Max dV/dt             | 40 V/us               |