



Click [here](#) for the 3D model.

| Dimensions |           |
|------------|-----------|
| Sheet Size | 240x240mm |
| L          | 240mm NOM |
| W          | 240mm NOM |
| T          | 0.1mm NOM |

| Packaging Specifications |                          |
|--------------------------|--------------------------|
| Tape Description         | Without PET Tape (Txx00) |
| Tape Thickness           | 0.03mm                   |
| Component Weight         | 18.74 g                  |

| General Information |   |
|---------------------|---|
| Series              | FF1   |
| Style               | Sheet   |
| Description         | Flex Suppressor Flame Retardant Type              |
| Features            | Flame Retardant Type                              |
| RoHS                | Yes   |
| Qualifications      | UL94 V-0, UL File No.E176124, AEC-Q200            |
| Environment         | RoHS Compliant, Halogen Free, PVC Free, Lead Free |

| Specifications       |                |
|----------------------|----------------|
| Temperature Range    | -40/+125°C     |
| Permeability         | 100 u At 3MHz  |
| Effective Frequency  | 1 MHz to 3GHz  |
| Specific Gravity     | 3.1 TYP        |
| Thermal Conductivity | 1.36 typical   |
| Surface Resistivity  | 1 MOhm/sq. TYP |