

G83-6744 Smart Card Keyboards

Full QWERTY Keyboard with Integrated FIPS 201 Certified Smart Card Reader



Actual product may vary from picture shown

Cable Length

Approx. 1.75 m

Facts & Features

- Secure PIN entry (class 2 reader)
- PC/SC smart card reader
- CT-API support
- Protocols T=0, T=1, S=8, S=9 and S=10
- EMV 2000 Terminal level 1 approved
- CCID compliant
- Compliant with ISO 7816
- Individual and easy key assignment due to our KeyM@n Software with new, comfort functions
- CAC certified and FIPS 201 certified

Dimensions

Keyboard: 458 x 195 x 54 mm
Keyboard: 18.0 x 7.28 x 2.13 inches
Packaging: 493 x 255 x 58 mm
Packaging: 19.83 x 10.04 x 2.28 inches

Packaging Unit

40 keyboards per master carton
80 master cartons per pallet

Keyswitch Lifetime:

20 million operations

System Requirements

USB Connection

Technical Data

Interface

USB full speed

Current consumption:

max. 100 mA

Number of Keys

104 = International key layout

Weight (without/with packaging)

approx. 1250 g / 2.76 lbs (without packaging)
approx. 2300 g / 5.07 lbs (with packaging)

Smart Card Clock

4.8 MHz

Storage Temperature

-20°C to 60°C

Operating Temperature:

0°C to 50°C

Agency Approvals / Instructions

CE, GS, VDE/GS, FCC Class B, cURus, c-tick,
VCCI, USB 2.0, EMV 2000 level 1, Microsoft
Windows®, FIPS 201

Delivery Volume

1 Smart Card Keyboard
1 Printed Manual
1 CD ROM

Warranty

2 Years

Order Description

Order Number	Interface	Color
G83-6744LUAUS-0	USB	Lt. Grey
G83-6744LUAUS-2	USB	Black

Available in various country versions upon request.

ZF Electronics Corporation
11200 88th Avenue
Pleasant Prairie, WI 53158
USA
Phone: 262.942.6500
Internet: www.cherrycorp.com

E-Mail: cep_sales@zf.com
Fax: 262.942.6566

The manufacturer accepts no liability for errors or non-availability, and reserves the right to change specifications without prior notice. Technical data relates to product specifications only. Features may differ from those described. Only drawings combined with product specifications shall be deemed binding.

© 2009 ZF Electronics Corporation, Last update: February 17, 2012_V01

