



AS-Interface module, A/B slave, 4 inputs and 3 outputs, black, Spring-type terminal (Push-in), for input/output, for floor mounting

<b>product brand name</b>	SIRIUS ACT
<b>product designation</b>	AS-Interface module
<b>product type designation</b>	3SU1
<b>General technical data</b>	
<b>product function</b>	4 DI / 3 DQ AB
<b>degree of pollution</b>	3
<b>type of voltage</b>	
• of the operating voltage	DC
• of the input voltage	DC
<b>consumed current maximum</b>	150 mA
<b>protection class IP</b>	IP20
<b>shock resistance for railway applications according to EN 61373</b>	Category 1, Class B
<b>vibration resistance for railway applications according to EN 61373</b>	Category 1, Class B
<b>reference code according to IEC 81346-2</b>	K
<b>Substance Prohibitance (Date)</b>	10/01/2014
<b>design of the slave type</b>	4 DI / 3 DQ AB
<b>AS-Interface slave profile</b>	S-7.A.E
<b>ID1 code</b>	0...7
<b>number of AS-i slaves</b>	1
protocol is supported ASIsafe (Safety at work) protocol	No
<b>operating voltage rated value</b>	18 ... 31.6 V
<b>operating voltage 1 at DC rated value</b>	30 V
<b>Communication/ Protocol</b>	
protocol is supported AS-Interface protocol	Yes
<b>Inputs/ Outputs</b>	
<b>number of digital inputs</b>	4
• safety-related	0
<b>number of digital outputs</b>	3
<b>Connections/ Terminals</b>	
<b>type of electrical connection</b>	spring-loaded terminal (push-in)
<b>type of connectable conductor cross-sections</b>	
• solid without core end processing	1x (0.14 ... 0.5 mm <sup>2</sup> )
• finely stranded without core end processing	1x (0.2 ... 0.5 mm <sup>2</sup> )
• at AWG cables	1x (26 ... 20)
<b>Product Function</b>	
suitability for use safety-related circuits	No
<b>Ambient conditions</b>	

<b>ambient temperature</b>	
<ul style="list-style-type: none"> <li>during operation</li> <li>during storage</li> </ul>	-25 ... +70 °C -40 ... +80 °C
environmental category during operation according to IEC 60721	3M6, 3S2, 3B2, 3C3 (without salt spray), 3K6 (with relative humidity of 10 ... 95%, no condensation in operation permitted)

### Installation/ mounting/ dimensions

<b>fastening method</b>	
<ul style="list-style-type: none"> <li>of modules and accessories</li> <li>of AS-i slaves</li> </ul>	Floor mounting Floor mounting
<b>height</b>	57.5 mm
<b>width</b>	23.8 mm
<b>depth</b>	53.5 mm

### Certificates/ approvals

<b>General Product Approval</b>	<b>EMC</b>	<b>Declaration of Conformity</b>
---------------------------------	------------	----------------------------------

[Confirmation](#)



<b>Test Certificates</b>	<b>other</b>
--------------------------	--------------

[Special Test Certificate](#)

[Type Test Certificates/Test Report](#)

[Confirmation](#)

[Environmental Confirmations](#)

### Further information

**Information- and Downloadcenter (Catalogs, Brochures,...)**

<https://www.siemens.com/ic10>

**Industry Mall (Online ordering system)**

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3SU1400-2EJ10-6AA0>

**Cax online generator**

<http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=3SU1400-2EJ10-6AA0>

**Service&Support (Manuals, Certificates, Characteristics, FAQs,...)**

<https://support.industry.siemens.com/cs/ww/en/ps/3SU1400-2EJ10-6AA0>

**Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)**

[http://www.automation.siemens.com/bilddb/cax\\_de.aspx?mlfb=3SU1400-2EJ10-6AA0&lang=en](http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=3SU1400-2EJ10-6AA0&lang=en)

last modified:

1/27/2022