



Click [here](#) for the 3D model.

Dimensions

| | |
|----|-----------------|
| D | 66.6mm +/-1mm |
| L | 106mm +/-1mm |
| T | 3.8mm NOM |
| S | 28.5mm +/-0.5mm |
| F | 15mm +/-0.5mm |
| DT | 15mm NOM |
| G | 13mm NOM |
| LT | 113mm +/-1mm |
| Z | 13mm NOM |

Packaging Specifications

| | |
|--------------------|-----------|
| Sleeving | Yes |
| Packaging | Bulk, Bag |
| Packaging Quantity | 12 |

General Information

| | |
|------------------|---|
| Series | PEH169_105 |
| Dielectric | Aluminum Electrolytic |
| Description | Screw Terminal, Aluminum Electrolytic |
| RoHS | Yes |
| Mounting | Stud |
| AEC-Q200 | No |
| Halogen Free | Yes |
| Component Weight | 415 g |
| Notes | Dimensions D And L Include Sleeving. M5. MS = M12x16. |

Specifications

| | |
|-----------------------|---|
| Capacitance | 1,500 uF |
| Capacitance Tolerance | -10/+30% |
| Voltage DC | 350 VDC |
| Temperature Range | -40/+105°C |
| Rated Temperature | 105°C |
| Life | 10000 Hrs (Rated Voltage And Ripple Current At 105C) |
| Resistance | 60 mOhms (100Hz 20C), 33 mOhms (100kHz 20C) |
| Ripple Current | 5.5 Amps (100Hz 105C), 30.6 Amps (10kHz 50C), 23.5 Amps (10kHz 40C) |
| Leakage Current | 5575 uA (5min 20°C) |
| Inductance | 16 nH (ESL) |