

## Timer

### Timing

Function: On Delay

Selectable Timing Ranges:

Instantaneous

0.1 to 1 Sec.

1 to 10 Sec.

0.1 to 1 Min.

1 to 10 Min.

0.1 to 1 Hr.

1 to 10 Hrs.

Repeat Accuracy: 1%+20mSec.

Knob setting error: 10%

Reset Time: 100mSec. (Max.)

### Electrical

Supply Voltages:

24, 120 & 240VAC, 50/60Hz

24, 48 & 110VDC

Power Consumption:

1.9VA @ 110VAC

2.1VA @ 220VAC

1.1W @ 24VDC

### Contact Ratings

3 Amps @ 30VDC/240VAC

General Purpose

1 Amps @ 120 VAC

Inductive (Cos $\phi$ =.35)

1/4HP @ 240VAC Motor

### Ordering Information

**BAMI Model**  
TGM — **TGM** — **2C** — **B - 120VAC**

### Contact Form

**2C** - Double Pole

Double Throw

**4C** - Four Pole

Double Throw

### Termination

**B** - Blade

**C** - Circuit Board

### Coil Voltage

24VAC

**120VAC**

240VAC

24VDC

48VDC

110VDC



### Environmental

Temperature Rating:

-10°C to 40°C

Life:

Mechanical:

50,000,000 Operations

Electrical:

600,000 Operations

## Socket


### Specifications

Current Rating: 5 Amps



Voltage Rating: 250VAC

Mounting: DIN or Surface

### Connections



### Dimensions



### Ordering Information

**BAMI Model**  
SG — **SG - 14** — **B**

**Number of Terminals**  
14 - 14 Terminals

**Termination**  
**B** - Blade  
**C** - Circuit Board