



Part Number	Contact Area Plating Finish
K42X-A15S/P-A4N	Gold Flash (standard option)
K42X-A15S/P-A4N15	15u" Gold (15 option)
K42X-A15S/P-A4N30	30u" Gold (30 option)

Material and Finish

- Shell: Steel, nickel plated
- Insulator: PBT thermoplastic with glass-fiber reinforcement, UL94V-0 rated
Color: Black
- Contact Material:
Socket - Phosphor Bronze
Plug - Brass
- Contact Plating Options:
Standard: gold flash on mating end, tin on termination end, nickel underplate on entire contact
15 Option: 15u" gold on mating end, tin on termination end, nickel underplate on entire contact
30 Option: 30u" gold on mating end, tin on termination end, nickel underplate on entire contact

Electrical Specifications

- Rated Current: 1.2A
- Rated Voltage: 30V RMS
- Insulation Resistance: more than 1000 megohms at 500V DC
- Contact Resistance: 13 milliohms max.
- Dielectric Withstanding Voltage: 1000V for 1 minute
- Operating Temperature: -55°C to +105°C

RoHS COMPLIANT



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	11/09/09	New Drawing	S. Vien	H. MA	S. Vien	09/30/09
A2	12/31/17	ECO #17-037	J. Elbanna	C. Furumasu		
A3	03/07/19	ECO #19-020	H. MA	D. Shehan		

K42X-A15S/P-A4N

Stacked D-Sub, 15 Female/15 Male, RoHS Compliant

0.750" Spacing, Boardlocks

