



Main

| | |
|------------------------------|---|
| Range of Product | Harmony 9001KY |
| Product or Component Type | Control station |
| Device short name | 9001KY |
| Provided equipment | Label plate START |
| Electrical circuit type | Motor |
| Contact block name | KA1 |
| Product Specific Application | For hoisting and mechanical handling applications |
| Level or class | Class II Division 2 Group G Class III |

Complementary

| | |
|-----------------------------------|---|
| Enclosure/cubicle description | Wall-mounted enclosure 1 cut-out Ø 30 mm |
| Enclosure material | Die cast zinc alloy Gray |
| Type of Installation | Indoor/outdoor |
| Control station composition | 1 push-button momentary 1 NO + 1 NC |
| Mechanical interlocking | Without mechanical interlock |
| Connector Type | Screw clamp connector |
| Connections - terminals | Direct connection AWG 2) solid stranded Direct connection AWG 12) solid stranded Direct connection AWG 24) solid stranded |
| [Ue] rated operational voltage | 300 V |
| [Ie] rated operational current AC | 10 A |

Environment

| | |
|---------------------------------------|--|
| NEMA Degree of Protection | NEMA 1 NEMA 13 NEMA 3 NEMA 4 |
| Environmental characteristic | Dust and oil resistant Resistant against immersion in water |
| Product Certifications | UL Listed |
| Ambient Air Temperature for Operation | -13...140 °F (-25...60 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |

Ordering and shipping details

| | |
|-----------------------|-----------------------------|
| Category | 21426-9001 K (NOT KA,KM,KX) |
| Discount Schedule | CS1 |
| GTIN | 785901513377 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 2.90 lb(US) (1.315 kg) |
| Returnability | No |
| Country of origin | MX |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Packing Units

| | |
|------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 12.70 in (32.258 cm) |
| Package 1 width | 5.00 in (12.7 cm) |
| Package 1 Length | 32.26 in (81.935 cm) |

Offer Sustainability

| | |
|----------------------------|--|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Nickel compounds, which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Toxic heavy metal free | Yes |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|