


CG 300 PG METAL CABLE GLANDS

PG THREAD

Impact resistant, suitable for industrial applications, water tight, corrosion resistant.



Technical details:

Material:	Brass, Nickel Plated
Clamping insert:	Polyamide 6
Seal:	Chloroprene (CR)
O-Ring:	Neoprene (NBR)
Protection class:	IP 68 - 5 Bar
Temperature range	
<i>permanent:</i>	-20°C to +100°C
<i>intermittent:</i>	-40°C to +150°C
Flammability:	V2 (according to UL 94)
Approvals:	cURus, cULus, DNV-GL, CE

Part Number	Thread Type	Clamping Range Ø min-max		Thread Diameter (TD)		Wrenching Flats Cap (SW1)		Thread Length (TL)	Height (H)	UL
		inches	mm	inches	mm	inches	mm			
PG										
MPS-7R	PG 7	.079 - .197	2.0 - 5.0	0.492	13	0.551	14	0.236	0.866	-
MPS-7	PG 7	.118 - .256	3.0 - 6.5	0.492	13	0.551	14	0.236	0.866	UR
MPS-9R	PG 9	.079 - .236	2.0 - 6.0	0.598	15	0.669	17	0.236	0.925	-
MPS-9	PG 9	.157 - .315	4.0 - 8.0	0.598	15	0.669	17	0.236	0.925	UR
MPS-11R	PG 11	.118 - .276	3.0 - 7.0	0.732	19	0.787	20	0.236	1.024	-
MPS-11	PG 11	.197 - .394	5.0 - 10.0	0.732	19	0.787	20	0.236	1.024	UR
MPS-13R	PG 13.5	.197 - .355	5.0 - 9.0	0.803	20	0.866	22	0.256	0.965	-
MPS-13	PG 13.5	.236 - .472	6.0 - 12.0	0.803	20	0.866	22	0.256	0.965	UL
MPS-16R	PG 16	.276 - .473	7.0 - 12.0	0.886	23	0.945	24	0.256	1.102	-
MPS-16	PG 16	.394 - .551	10.0 - 14.0	0.886	23	0.945	24	0.256	1.102	UL
MPS-21R	PG 21	.354 - .630	9.0 - 16.0	1.114	28	1.181	30	0.283	1.280	-
MPS-21	PG 21	.512 - .709	13.0 - 18.0	1.114	28	1.181	30	0.283	1.280	UL
MPS-29R	PG 29	.472 - .788	12.0 - 20.0	1.457	37	1.575	40	0.315	1.547	-
MPS-29	PG 29	.709 - .984	18.0 - 25.0	1.457	37	1.575	40	0.315	1.547	UL
MPS-36R	PG 36	.788 - 1.024	20.0 - 26.0	1.850	47	1.969	50	0.354	1.890	-
MPS-36	PG 36	.866 - 1.260	22.0 - 32.0	1.850	47	1.969	50	0.354	1.890	UL
MPS-42R	PG 42	.984 - 1.220	25.0 - 31.0	2.126	54	2.283	58	0.472	1.909	-
MPS-42	PG 42	1.182 - 1.496	30.0 - 38.0	2.126	54	2.283	58	0.472	1.909	UL
MPS-48R	PG 48	1.142 - 1.378	29.0 - 35.0	2.335	59	2.520	64	0.551	2.087	-
MPS-48	PG 48	1.339 - 1.732	34.0 - 44.0	2.335	59	2.520	64	0.551	2.087	UL
PG with Long Thread										
MPS-7L	PG 7	.118 - .256	3.0 - 6.5	0.492	12.5	0.551	14	0.394	0.858	UR
MPS-9L	PG 9	.157 - .315	4.0 - 8.0	0.598	15.2	0.669	17	0.394	0.890	UR
MPS-11L	PG 11	.197 - .394	5.0 - 10.0	0.732	18.6	0.787	20	0.394	0.996	UR
MPS-13L	PG 13.5	.236 - .472	6.0 - 12.0	0.803	20.4	0.866	22	0.394	0.949	UL
MPS-16L	PG 16	.394 - .551	10.0 - 14.0	0.886	22.5	0.945	24	0.394	1.083	UL
MPS-21L	PG 21	.512 - .709	13.0 - 18.0	1.114	28.3	1.181	30	0.472	1.228	UL
MPS-29L	PG 29	.709 - .984	18.0 - 25.0	1.457	37.0	1.575	40	0.472	1.547	UL
MPS-36L	PG 36	.866 - 1.260	22.0 - 32.0	1.850	47.0	1.969	50	0.551	1.858	UL
MPS-42L	PG 42	1.182 - 1.496	30.0 - 38.0	2.126	54.0	2.283	58	0.63	1.878	UL
MPS-48L	PG 48	1.339 - 1.732	34.0 - 44.0	2.335	59.3	2.520	64	0.709	2.047	UL