



SIGN	DATE	DESCRIPTION	APPROVER
△			
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item 1 Terminal housing : Thermoplastic (UL 94V-0)
- Item 2 Clamp : Steel stamping , Zinc plated
- Item 3 Wire guard solder pin : Copper, Tin plated
- Item 4 Terminal screw : Steel , Zinc plating" - "slot type

Electrical cULus IEC

- Voltage rating : 300V 1000V
- Current rating : 65A 76A
- Wire range : 16.00mm
- Solid wire (AWG) : 6-20
- Stranded wire (AWG) : 6-20
- Torque (LB-In.) : 19LB-In
- Screw : M4.5
- Wire strip length : 10-11mm
- Withstanding voltage : 2.2KV 6KV
- Operating temperature : -40°C+115°C
- Soldering temperature : 250°C+10°C/5 Sec
- Safety Approval : US

VP xx 85 x 8 xxxx G

- | | | | |
|----------------|-----------------------|--|--------------|
| 02 2 CONTACTS | 0: Black | 0000 Standard @ Logo | RoHS |
| 03 3 CONTACTS | 5: Green (RAL 6018/T) | 000A Standard ANY Logo | Pb<40,000ppm |
| ... | 6: Blue | Any special item by customer request, please contact sales department. | |
| 12 12 CONTACTS | 8: Grey (RAL 7035/D) | | |

Poles	02	03	04	05	06	07	08	09	10	11	12
Dim L	25.40	38.10	50.80	63.50	76.20	88.90	101.60	114.30	127.0	139.70	152.40
Dim B	12.70	25.40	38.10	50.80	63.50	76.20	88.90	101.60	114.30	127.0	139.70
TOL	±0.15			±0.20			±0.30				

ANYTEK				CUSTOMER COPY			
<small>ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD</small>							
TITLE		VP 12.70 Series (0.9x1.0) Contacts Pin Pitch 4.0mm ----Double parallel tail					
PART NO.		VPxx85x8xxxxG			DWG NO.		8VP0120
APPROVED		CHECKED		DESIGNED		DRAWN	
		Aaron 2009.11.16		Aaron 2009.11.16		CUST NO.	
						Tolerance	
						X. ±0.50	
						X.X ±0.30	
						X.XX ±0.10	
						X° ±1°	
				SHEET: 01/01		REV.: B	