

## ROL0 RMA Tack Flux (for Leaded) in 10cc/10g Luer Lock Manual Syringe w/tips

### Product Highlights

Tack Flux Rosin Mildly Activated (RMA)

Used for touch up and rework, attachment of BGA spheres, and soldering flip chip components.

Low viscosity synthetic

**RoHS 3 and REACH compliant**



Representative Photo Only  
Please note flux color may vary from light yellow to orange/brown

### Specifications

|                              |  |
|------------------------------|--|
| Flux Type:                   | Synthetic RMA (for Leaded applications)            |
| Flux Classification:         | ROL0   |
| Flux Activation Temperature: | 140°C (284°F)                                      |
| Color:                       | Light yellow to orange/brown                       |
| Packaging:                   | 10cc/10g Luer Lock Manual Syringe                  |
| Shelf Life:                  | Refrigerated >24 months, Unrefrigerated >24 months |

### Stencil Life

>8 hours @ 20-50% RH 22-28°C (72-82°F)

>4 hours @ 50-70% RH 22-28°C (72-82°F)

### Stencil Cleaning

Automated stencil cleaning systems for both stencil and misprinted boards. Manual cleaning using isopropyl alcohol (IPA).

### Storage and Handling

Store refrigerated or at room temperature 3-25°C (37-77°F). Do not freeze. Allow 4 hours for flux to reach an operating temperature of 20-25°C (68-77°F) before use.

### Transportation

This product has no shipping restrictions. Shipping below 0°C (32°F) or above 25°C (77°F) for normal transit times by ground or air will not impact this product's stated shelf life.

### Conforms to the following Industry Standards:

J-STD-004B, Amendment 1 (Solder Fluxes):

Yes

RoHS 3 Directive (EU) 2015/863:

Yes