

Specification Sheet

Part Number: 115-00054



Releasable Cable Tie, Release Lever, 9.8" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg

| | |
|---------------------|---|
| Article Number | 115-00054 |
| Type | RF250 |
| Color | Natural (NA) |
| Features & Benefits | <ul style="list-style-type: none">•Release feature allows maintenance or changeouts as needed.•Polyamide 6.6 cable ties deliver excellent resistance to chemicals and salts.•Inside serrations provide strong grip on cables and wire bundles.•Reliable bundle fastening plus low insertion force for ease of use. |
| Quantity Per | bag |

Product Description

Releasable Cable Ties feature an integrated release mechanism on the head, allowing for changeouts without destroying the cable tie. The head design ensures consistently high tensile strength, even after repeated use. Rounded tail glides into head with low insertion force.

Short Description

Releasable Cable Tie, Release Lever, 9.8" Long, 50lb Tensile Strength, PA66, Natural, 100/pkg

Global Part Name

RF250-PA66-NA

Minimum Tensile Strength (Imperial)

50.0

Minimum Tensile Strength (Metric)

222.3

Length L (Imperial)

9.8

Length L (Metric)

250.0

Identification Plate Position

none

Releasable Closure

Yes

Width W (Imperial)

0.29

Width W (Metric)

7.4

Bundle Diameter Min (Imperial)

0.1

Bundle Diameter Min (Metric)

2.5

Bundle Diameter Max (Imperial)

2.83

Bundle Diameter Max (Metric)

72.0

Thickness T (Metric)

1.2

| | |
|---------------------------------------|----------------------------------|
| Material | Polyamide 6.6 (PA66) |
| Material Shortcut | PA66 |
| Flammability | UL 94 V2 |
| Operating Temperature (Metric) | -40°F to +185°F (-40°C to +85°C) |
| ROHS Complaint | Yes |
| Package Quantity(Imperial) | 100 |
| Package Quantity (Metric) | 100 |
| Customs Number | 3926909988 |