

## Eaton 9PX 6000VA 5400W 208V Online Double-Conversion UPS - L6-30P, 2 L6-20R, 2 L6-30R, Hardwired Output, 10 ft. Input Cord, Cybersecure Network Card, Extended Run, 3U

MODEL NUMBER: 9PX6K-10



Provides sine wave output, complete battery backup and power protection for mission-critical IT installations, edge networks and other advanced network applications.

### Features

#### 6kVA/5.4kW/208V Battery Backup for IT Installations and Edge Networks

This 9PX rack-mount online double-conversion UPS system provides reliable battery backup and AC power protection against blackouts, brownouts, surges and line noise that can damage valuable IT equipment or destroy data. The 9PX6K-10 is superlative power management for education, commercial, financial or healthcare networking components, including Cisco switches and servers.

#### Expandable Internal Battery Backup Keeps You Operational Through Power Outages

The field-replaceable, hot-swappable valve regulated lead acid (VRLA) battery modules allow you to work through short power failures and give you enough time to safely save files and shut down your system in case of a prolonged blackout. Exclusive ABM technology increases battery life by 50 percent and closely monitors battery health to provide advanced notice when batteries need replacing. You can also connect up to four extended battery modules (9PXEBM180RT, sold separately) for hours of extended runtime.

#### Included Gigabit Network Interface Offers 24/7 Remote Access

The NETWORK-M2 Gigabit network card enables full remote configuration and management, including load shedding, reboots of connected equipment and safe shutdowns. UPS firmware can also be flashed remotely through the NETWORK-M2 without dropping the load, so you don't have to plan for downtime. The card meets both UL 2900-1 and IEC 62443-4-2 standards for cybersecurity, which were developed to address the vulnerability of connected devices to known malware/exploits and to protect business from these risks. The optional Environmental Monitoring Probe Gen 2 (EMPDT1H1C2, sold separately) provides a variety of environmental monitoring capabilities, including temperature and humidity conditions.

#### NEMA Outlets Protect Your Connected Components

Two L6-20R and two L6-30R managed outlets provide connected equipment with pure sine wave AC output and allow you to monitor power consumption down to the outlet group level. Power provided by these outlets is filtered to protect connected equipment against damaging surges and line noise. The 9PX6K-10 also supports hardwired output.

#### Rotating LCD Interface Keeps You Informed at a Glance

### Highlights

- Keeps equipment running during outages to allow time for file saves and safe shutdown
- Included NETWORK-M2 Gigabit network card enables full remote access and control
- Exclusive ABM technology with 3-stage charging increases internal battery life by 50%
- Interactive LCD interface keeps you updated on critical load information in real time
- Optional extended battery modules allow extended runtime to keep equipment powered

### Package Includes

- 6000VA 5400W 208V 9PX Online Double-Conversion UPS with 4 Outlets
- NETWORK-M2 Gigabit network card
- USB cable
- RS-232 cable
- Tower support stands
- Cable gland for hardwire connection
- Phillips-head screwdriver
- Rack-mounting hardware
- Owner's manual



Powering Business Worldwide

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

The front-panel LCD provides control settings and critical information to help diagnose any issues. The interface rotates to accommodate both rack-mount and tower configurations, and it tilts up to 45 degrees for more comfortable viewing.

**Advanced Communications Ports Allow for Automatic Saves and Shutdowns**

RS-232 and USB ports connect to a serial-enabled device for a variety of communication options (cables are included). A dry-contact relay port can be programmed through the LCD to provide reliable communications to automation and industrial components. The RPO/ROO connectors permit emergency shutdown or remote restart of all connected equipment.

**Versatile Installation Options**

You can mount the 9PX6K-10 in just 3U of space in an EIA-standard 19-inch rack using the included 4-post rail kit or an optional 2-post rail kit (RK2PC, sold separately). You can also adapt it for tower installation using the included support stands. The 10-foot power cord with NEMA L6-30P plug connects to a compatible AC outlet. A cable gland and Phillips screwdriver are included for alternate hardwire input.

## Specifications

| OVERVIEW                           |   |
|------------------------------------|---|
| UPC Code                           | 743172090522                                |
| UPS Type                           | On-Line                                     |
| INPUT                              |   |
| Input Phase                        | Single-Phase                                |
| Rated input current (Maximum Load) | 24.8A                                       |
| Nominal Input Voltage(s) Supported | 200V AC; 208V AC; 220V AC; 230V AC; 240V AC |
| UPS Input Connection Type          | L6-30P                                      |
| Input Circuit Breakers             | 20A   |
| UPS Input Cord Length (ft.)        | 10  |
| UPS Input Cord Length (m)          | 3.1   |
| Plug Type                          | L6-30P                                      |
| OUTPUT                             |   |
| Output Capacity (VA)               | 6000  |
| Output Capacity (kVA)              | 6   |
| Output Capacity (Watts)            | 5400  |
| Output Capacity (kW)               | 5.4   |
| Power Factor                       | 0.9   |
| Crest Factor                       | 3:1   |
| Nominal Voltage Details            | 200V, 208V, 220V, 230V, 240V                |
| Frequency Compatibility            | 50 / 60 Hz                                  |



Powering Business Worldwide

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

|   |   |
|---|---|
| Output AC Waveform (Battery Mode)                             | Pure Sine wave  |
| Nominal Output Voltage(s) Supported                           | 200V; 208V; 220V; 230V; 240V  |
| Output Receptacles  | (2) L6-20R; (2) L6-30R; Hardwire  |
| Individually Controllable Load Banks                          | Yes   |
| <b>BATTERY</b>  |   |
| Battery Type  | Valve Regulated Lead Acid (VRLA)  |
| Runtime Full Load (min.)                                      | 3 min.  |
| Runtime Half Load (min.)                                      | 8 min.  |
| Expandable Runtime  | Yes   |
| Expandable Runtime Description                                | Add up to 4 EBM maximum   |
| DC System Voltage (VDC)                                       | 180   |
| Battery Access  | Battery access door   |
| Internal UPS Replacement Battery Cartridge                    | &nbsp;<a class="productLink" href="//tripplite.eaton.com/replacement-battery-for-eaton-9px-3kva-6kva-ups-ebm-744-A1974">744-A1974</a>&nbsp;     |
| Battery Replacement Description                               | Hot-swappable, user replaceable batteries. UPS requires 1 Replacement Battery Cartridge.  |
| Battery Management  | ABM technology (3-stage charging extends battery service life by 50% and provides advance warning for battery replacement)                      |
| <b>USER INTERFACE, ALERTS &amp; CONTROLS</b>                  |   |
| Front Panel LCD Display                                       | LCD graphical display   |
| Switches  | RPO / ROO   |
| Alarm Cancel Operation  | Press ESC to silence the alarm  |
| Audible Alarm   | Audible alarm indicates utility failure, low-battery, overload, other UPS/Battery fault or remote shutdown conditions                           |
| <b>SURGE / NOISE SUPPRESSION</b>                              |   |
| UPS AC Suppression Response Time                              | 0 ms  |
| EMI / RFI AC Noise Suppression                                | Yes   |
| <b>PHYSICAL</b>   |   |
| Primary Form Factor   | Rackmount; Tower  |
| Rack Height   | 3U  |
| Cooling Method  | Fan   |
| Installation Form Factors Supported with Included Accessories | 4 post 19 inch rackmount  |
| Installation Form Factors Supported with Optional Accessories | 2 post rackmount (&nbsp;<a class="productLink" href="//tripplite.eaton.com/eaton-2-post-rack-mount-rail-kit-for-9px-ups-RK2PC">RK2PC</a>&nbsp;) |



Powering Business Worldwide

1000 Eaton Boulevard  
Cleveland, OH 44122  
United States

|   |   |
|---|---|
| Minimum Required Rack Depth (cm)              | 81.28   |
| Minimum Required Rack Depth (inches)          | 32  |
| Unit Dimensions (hwd / in.)                   | 5.100 x 17.300 x 28.400   |
| Unit Weight (lbs.)                            | 106.000   |
| Unit Weight (kg)                              | 48.08   |
| <b>ENVIRONMENTAL</b>                          |   |
| Operating Temperature Range                   | 32° to 104°F (0° to 40°C)   |
| Relative Humidity                             | 0-95% non-condensing  |
| AC Mode Efficiency Rating (100% Load)         | 93  |
| AC Economy Mode Efficiency Rating (100% Load) | 98  |
| <b>COMMUNICATIONS</b>                         |   |
| Network Management Cards                      | &nbsp;<a class="productLink" href="//tripplite.eaton.com/eaton-secure-gigabit-network-card-for-ups-systems-NETWORK-M2">NETWORK-M2</a>&nbsp;; &nbsp;<a class="productLink" href="//tripplite.eaton.com/eaton-industrial-gateway-card-mini-slot-for-ups-systems-INDGW-M2">INDGW-M2</a>&nbsp;; &nbsp;<a class="productLink" href="//tripplite.eaton.com/eaton-relay-serial-interface-card-RELAY-MS">RELAY-MS</a>&nbsp; |
| Communications Interface                      | Pre-installed network card; RS-232; USB   |
| <b>APPLICATIONS</b>                           |   |
| UPS Applications                              | Mission Critical Applications   |
| <b>STANDARDS &amp; COMPLIANCE</b>             |   |
| Product Certifications                        | NOM (Mexico); EN 62040-2; cUL Listed  |
| Product Compliance                            | FCC Part 15 Class A (USA); CE (Europe); FCC (USA); RoHS   |
| <b>WARRANTY &amp; SUPPORT</b>                 |   |
| Product Warranty Period (U.S. & Canada)       | 2-year limited warranty   |
| Extended Service Plans                        | <b>ADVANCED DEPOT EXCHANGE</b> 5-YEAR DEPOT REPAIR: 9SW5Y-6000UCExpedited parts coverage for 5 yearsParts, electronics and UPS batteries coverageNext business day shippingTechnical support <b>5-YEAR ON-SITE PLAN: WFLN75XX-6009UC</b> On-site parts and labor coverage for years 5Parts, electronics and UPS batteries coverage24x7 on-site labor coverage, next-day responseNext-day shippingTechnical support  |



Powering Business Worldwide

© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.