



General Information		
Series	ACA Indust COG HT200C	
RoHS	No	
Prop 65	WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.	
SCIP Number	a54cd522-25fb-4dac-afe5-a404d68708e3	
Termination	Gold	
Failure Rate	N/A	
AEC-Q200	No	
Notes	Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk.	

Specifications				
Capacitance	1000 pF			
Capacitance Tolerance	5%			
Voltage DC	100 VDC			
Dielectric Withstanding Voltage	250 VDC			
Temperature Range	-55/+200°C			
Temperature Coefficient	COG			
Dissipation Factor	0.15% 1 kHz 1.0Vrms			
Insulation Resistance	100 GOhms			

Click here for the 3D model.

Dimensions	
L	6.86mm MAX
W	2.54mm MAX
Т	2.54mm MAX
LL	3.175mm MIN
F	0.508mm +/-0.051mm

Packaging Specifications	/
Packaging	Bulk, Bag
Packaging Quantity	1

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.