



213754
SBT-RGB-R50-4S-B5
Signal column

- Status display 360°
- Strong signal effect thanks to state-of-the art, high-efficiency LEDs
- Low energy consumption
- Can be used immediately thanks to three trigger inputs (eight predefined/user-defined color settings)
- Freely configurable functions via IO-Link (process data)
- Simple installation (M30 threading)



BN 1 ⊕
 WH 2 Trigger 1
 BK 4 ⊖ Trigger 3
 BU 3 ⊖
 GY 5 Trigger 2

Legende / Legend:
 >RT< = Rot langsam blinkend / flashing red slowly
 >>RT<< = Rot blitzend / rapidly flashing red
 >BUZ< = Buzzer intermittierend / Buzzer intermittent (1Hz)
 >>BUZ<< = Buzzer intermittierend / Buzzer intermittent (2,5Hz)

All Trigger Inputs have a delay ~50 ms.
 Pre-sets can be defined via IO-Link.

TRIG 1	TRIG 2	TRIG 3	Pre-Set	Factory setting (Seg 1 / Seg 2 / Seg 3 / Seg 4 / BUZ)			
				Var. 4S		Var. 4B	
0	0	0	1	--	--	--	--
1	0	0	2	--	--	RT	--
0	1	0	3	--	GN	--	GN
1	1	0	4	--	YE	--	YE
0	0	1	5	BU	--	--	BU
1	0	1	6	WH	--	--	WH
0	1	1	7	--	--	>RT<	>BUZ<
1	1	1	8	--	--	>>RT<<	>>BUZ<<

BK: black BU: blue GY: grey YE: yellow
 BN: brown GN: green WH: white

Function										

Technical data (typ.)		+20°C, 24 V DC
Service voltage		18 ... 30 V DC (Supply Class 2)
Internal power consumption		230 mA (24 V DC)
Power		5,5 W (24 V)
Inverse polarity protection		Yes
Illuminated area		50 x 37 mm (Ø x H / segment)
Number of segments		4
Housing material		Aluminum (natural, Anodized)
Material		Polycarbonate (Diffusor)
Weight		310 g
Protection class		III, operation on protective low voltage
Risk group (DIN EN 62471)		Free group
Model		Signal column
Operating modes		External trigger / segment mode / level mode / demo mode, LED operating modes: Static / Blinking / Flashing
Color selection		Red, green, yellow, blue, white, orange, pink, user-defined
Light intensity can be adjusted		10 to 100 %, via IO-Link
Trigger input high level		> 8,0 V
Trigger input low level		< 5,0 V
Trigger input		8 color presets: selectable via trigger 1 + 2 +3

**213754****SBT-RGB-R50-4S-B5****Signal column****Technical data (typ.)****+20°C, 24 V DC**

Interface

- IO-Link (V1.1, COM2 38,4 kBd, 5 000 µs)
- for parameterization (process data)

Color

RGB

Vibration load

10 ... 55 Hz / 0,35 mm

Ambient temperature during operation

0 ... +50 °C

Protection type

IP 65

Connection

Connector, M12, 5-pin

More information / accessories<https://www.di-soric.com/213754>