




ACA Indust COG HT200C, Ceramic, 0.047 uF, 5%, 100 VDC, COG



Click here for the 3D model.

Dimensions	
L	18.29mm MAX
W	9.4mm MAX
Т	4.06mm MAX
LL	3.175mm MIN
F	0.635mm +/-0.051mm

Packaging Specifications			
Packaging	Bulk, Bag		
Packaging Quantity	1		

General Information			
Series	ACA Indust COG HT200C		
RoHS	No		
Prop 65	▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.		
SCIP Number	40ca96cd-0c4f-422c-81f6-c154f87d1084		
Termination	Lead (SnPb)		
Failure Rate	N/A		
AEC-Q200	No		
Notes	Lead Length Shown Is For Parts Supplied In Bulk, See Packaging Specifications For Lead Lengths When Not Provided In Bulk.		

Specifications	
Capacitance	0.047 uF
Capacitance Tolerance	5%
Voltage DC	100 VDC
Dielectric Withstanding Voltage	250 VDC
Temperature Range	-55/+200°C
Temperature Coefficient	COG
Dissipation Factor	0.15% 1 kHz 1.0Vrms
Insulation Resistance	21.2766 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.