

R474N3180DQA1K

Aliases (474N3180DQA1K)

Not for New Design

General Information

Series

Dielectric

R47 X1 440 VAC, Film, Metallized Polypropylene, Automotive Safety, 0.18 uF, 10%, 440 VAC (X1), 1000 VDC, 110°C, Lead Spacing = 22.5mm



Style Radial Automotive Grade, EMI Safety Features RoHS Yes Lead Wire Leads Safety Class X1 AEC-Q200, ENEC, UL, cUL Qualifications AEC-Q200 Yes **THB** Performance Yes **Component Weight** 6.608 g

R47 X1 440 VAC

Metallized Polypropylene

| Specifications | 1 |
|-----------------------|--------------|
| Capacitance | 0.18 uF |
| Capacitance Tolerance | 10% |
| Voltage AC | 440 VAC (X1) |
| Voltage DC | 1000 VDC |
| Temperature Range | -40/+110°C |
| Rated Temperature | 110°C |
| Dissipation Factor | 0.1% 1kHz |
| Insulation Resistance | 100 GOhms |
| Max dV/dt | 300 V/us |

Click here for the 3D model.

| Dimensions | |
|------------|--------------------|
| L | 26.5mm +0.3/-0.5mm |
| Н | 18.5mm +0.1/-0.5mm |
| т | 10mm +0.2/-0.5mm |
| S | 22.5mm +/-0.4mm |
| НО | 18.5mm +/-0.5mm |
| F | 0.8mm +/-0.05mm |

Packaging Specifications

Packaging Packaging Quantity Ammo, 360x340x59mm, Box 235

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.