

VIEW ON MATING SIDE

U	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A
∞															
◁	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A

1 2 3 4 5 6 7 8 9 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27 28 29 30 31 32

A = 32 STANDARD CONTACTS L-2,9

Marking	Standard
Performance level	G2/0 = Contact area level2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85042-0002 sht.1
Technical Data	PS-85042-0001

A	G2/0	a1-16	c1-16
Contact symbol	Perform. level	Contact position number	

first release see ECN No. 2154	REVISIONS		FOR PREVIOUS REVISIONS SEE MRI LIST	
	REVISIONS			
LTR	DESIGN DIMENSION		EQUIVALENT DIMENSION	
	<input type="checkbox"/> MM <input type="checkbox"/> IN.		<input type="checkbox"/> MM <input type="checkbox"/> IN.	
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS			
	3 PLACE ± .		±	
	2 PLACE ± .		±	
	1 PLACE ± .		±	
	UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 2° INCH METRIC			
	DRWG BY	CHK'D BY	APP'D BY	SCALE
	Cc	KN		
	SIGN	SIGN	SIGN	
	DRWG PROJECT NAME	CAD/CAM PROJECT NAME		
	s8504200	s8504200		
	s71	s71		
	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			
	TITLE		SHEET NO. DATE	
	48 pos. female connector acc. DIN 41612 style C/2 contacts arrangement		1 OF 1 96/05/23	
	MOLEX EUROPE		DWG NO. SDA-85042-0074	
	PART NO. 85042-0074		SIZE A	