

CKC18X512FDGAC7210

KC-LINK Auto COG, Ceramic, 5100 pF, 1%, 1000 VDC, COG, SMD, MLCC, FT-CAP, Ultra-Stable, 1812



Click here for the 3D model.

Dimensions	
Chip Size	1812
L	4.5mm +/-0.4mm
W	3.2mm +/-0.3mm
Т	1.25mm +/-0.15mm
В	0.7mm +/-0.35mm

Packaging Specifications		
Packaging	T&R, 330mm, Plastic Tape	
Packaging Quantity	4000	

General Information		
Series	KC-LINK Auto COG	
Style	SMD Chip	
Description	SMD, MLCC, FT-CAP, Ultra-Stable	
Features	FT-CAP, Ultra-Stable	
RoHS	Yes	
Termination	Flexible Termination	
Marking	No	
Qualifications	AEC-Q200	
AEC-Q200	Yes	
Component Weight	67 mg	
Shelf Life	78 Weeks	
MSL	1	

Specifications	
Capacitance	5100 pF
Measurement Condition	1 kHz 1.0Vrms
Capacitance Tolerance	1%
Voltage DC	1000 VDC
Dielectric Withstanding Voltage	1200 VDC
Temperature Range	-55/+150°C
Temperature Coefficient	COG
Capacitance Change with Reference to +25°C and 0 VDC Applied (TCC)	30 ppm/C, 1kHz 1.0Vrms
Dissipation Factor	0.1% 1 kHz 1.0Vrms
Aging Rate	0% Loss/Decade Hour
Insulation Resistance	100 GOhms

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.