



The measurement position of Lead Spacing (S) and Width (V) is critical in straight lead capacitors.

Click [here](#) for the 3D model.

### Dimensions

|    |                 |
|----|-----------------|
| D  | 10mm MAX        |
| T  | 5mm MAX         |
| S  | 12.5mm +/-0.8mm |
| H0 | 16mm +/-0.5mm   |
| F  | 0.6mm +/-0.05mm |
| A  | 6mm MAX         |
| V  | 2.1mm +/-0.5mm  |

### Packaging Specifications

Packaging T&R, H0 = 16mm, Component Pitch = 25.4mm

### General Information

|                |  |
|----------------|--|
| Series         | ERP610 SFTY X1-760 Y1-500  |
| Style          | Radial Disc  |
| Description    | Ceramic Single Layer Safety Disc Capacitors  |
| RoHS           | Yes  |
| Termination    | Tin  |
| Qualifications | UL, CSA, CAN, ENEC, VDE  |
| AEC-Q200       | No   |
| Notes          | Please See Bulletin For Taping Information. H0 Dimension Refers to Seating Plane To Center Hole of Tape. |

### Specifications

|                         |                            |
|-------------------------|----------------------------|
| Capacitance             | 1500 pF                    |
| Capacitance Tolerance   | 10%                        |
| Voltage AC              | 760 VAC (X1), 500 VAC (Y1) |
| Temperature Range       | -40/+125°C                 |
| Temperature Coefficient | Y5U                        |
| Dissipation Factor      | 2.5%                       |
| Insulation Resistance   | 10 GOhms                   |
| Safety Class            | X1/Y1                      |