

## Power Extension Cord, NEMA 5-15P to NEMA 5-15R - 13A, 120V, 16 AWG, 10 ft. (3 m), Black

MODEL NUMBER: P022-010-13A



13-amp extension cord connects two devices with 5-15P/5-15R power connectors or extends your existing power connection.

### Features

#### 10-Foot Extension Cord Connects Monitors, Printers, Servers and Other Equipment

This power extension cable is designed for small data center or office workstation applications that do not require a heavy-gauge connection. With a NEMA 5-15P plug on one end and a NEMA 5-15R receptacle on the other, this UL listed (UL 817) cord can be used to power a printer or monitor, attach a rack server to a PDU or extend an existing connection up to 10 feet (3 meters). The 10-foot length allows you more flexibility in placing equipment with respect to the power outlet.

## Specifications

| OVERVIEW                    |   |
|-----------------------------|---|
| UPC Code                    | 037332275219                                      |
| Device Compatibility        | Computer; Monitor/HDTV; Printer; Server; UPS; PDU |
| Country/Region              | North America                                     |
| INPUT                       |   |
| Maximum Input Amps          | 13  |
| Voltage Compatibility (VAC) | 125   |
| PHYSICAL                    |   |
| Plug Color                  | Black   |
| Cable Jacket Color          | Black   |
| Cable Jacket Material       | PVC   |

### Highlights

- Recommended for powering printers, monitors and other essential peripherals
- Ideal for home/office applications, small server rooms and data centers
- Adds 10 ft. to your existing connection to provide more flexibility in placing devices
- UL listed cable is ideal replacement for worn-out or missing extension cord

### Package Includes

P022-010-13A Power Extension Cord, NEMA 5-15P to NEMA 5-15R, 10 ft. (3 m), Black

|                                      |                               |
|--------------------------------------|-------------------------------|
| Cable Jacket Rating                  | FT2                           |
| Power Cord Jacket Type               | SJT                           |
| Cable Outer Diameter (OD)            | 8.3mm                         |
| Number of Conductors                 | 3                             |
| Wire Gauge (AWG)                     | 16                            |
| Wire Gauge (OD - mm <sup>2</sup> )   | 1.31                          |
| Cable Length (ft.)                   | 10                            |
| Cable Length (m)                     | 3.05                          |
| Shipping Dimensions (hwd / in.)      | 14.17 x 11.80 x 0.50          |
| Shipping Dimensions (hwd / cm)       | 35.99 x 29.97 x 1.27          |
| Shipping Weight (lbs.)               | 0.77                          |
| Shipping Weight (kg)                 | 0.35                          |
| <b>ENVIRONMENTAL</b>                 |                               |
| Operating Temperature Range          | -4° to 140°F (-20° to 60°C)   |
| Storage Temperature Range            | -4° to 140°F (-20° to 60°C)   |
| Operating Humidity Range             | 20% TO 80% RH, NON-CONDENSING |
| Storage Humidity Range               | 20% to 80% RH, Non-Condensing |
| <b>CONNECTIONS</b>                   |                               |
| Side A - Connector 1                 | NEMA 5-15P                    |
| Side B - Connector 1                 | NEMA 5-15R                    |
| <b>FEATURES &amp; SPECIFICATIONS</b> |                               |
| Antibacterial                        | No                            |
| Angled Plug                          | No                            |
| High Voltage                         | No                            |
| Locking Plug                         | No                            |
| Coiled Power Cord                    | No                            |
| <b>STANDARDS &amp; COMPLIANCE</b>    |                               |
| Product Certifications               | cUL Listed; UL Listed         |
| Product Compliance                   | RoHS; REACH                   |
| <b>WARRANTY &amp; SUPPORT</b>        |                               |
| Product Warranty Period (Worldwide)  | Lifetime limited warranty     |



1000 Eaton Boulevard  
Cleveland, OH 44122  
United States



© 2023 Eaton. All Rights Reserved.  
Eaton is a registered trademark. All other trademarks  
are the property of their respective owners.