



LAYOUT SHOWN AS EXAMPLE

Keying Shown as example

| Connector dimension | |
|---------------------|----------|
| Dim | Nominal |
| ØS | 48 Max |
| Z | 31 Max |
| VV THREAD | M37x1-6g |

CHARACTERISTICS

- Standard : Based on MIL-DTL-38999 Series III
- Shell Material : Composite
- Shell Plating : Without Plating
- Insulator : Thermoplastic
- Contacts : Copper Alloy
- Seals & Grommet : Silicon Elastomer
- Contact Plating : Gold over copper Alloy 0.8µm minimum
- Durability : 500 Mating cycles
- Delivered without Souriau contacts
- Temperature Range : -65°C to +175°C
- Salt Spray : 2000 hours
- Mass : 48.9 g ± 10%

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| | |
|---------|-----------------------------|
| Country | Jurisdiction & Control List |
| FR | Not Listed |

PN: 8D525X61SBL

| | | | |
|--------------|---|--------------------------------|---|
| A | 17-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | Composite Plug 8D series | | |
| SCALE | | General linear Tolerances: ±-- | NPRDS / PROJECT 859 |
| NA | SOURIAU WWW.SOURIAU.COM | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | A3 | | SOURIAU DRG N° 8D525X61SBL-C SHEET 1/2 |

| | | | | | | | | | | |
|---------------|---------------------------|---|---|----|------------------------------------|----|---|---|---|------------------------|
| BASIC SERIES: | 8D | 5 | - | 25 | X | 61 | S | B | L | Delivered W/O Contacts |
| SHELL TYPE | : Plug with RFI Shielding | | | | ORIENTATION : B | | | | | |
| CONTACT TYPE | : Standard Crimp Contact | | | | CONTACT TYPE : SOCKET(500 Matings) | | | | | |
| SHELL SIZE | : 25 | | | | CONTACT LAYOUT : 25-61 | | | | | |
| PLATING | : X = Without Plating | | | | | | | | | |

Contact Layout



| Contacts (Insert arrangement 25-61) | | | | | |
|--|--------------|--------------|---------------------|--------------|--------------|
| Contact position ID | Location | | Contact position ID | Location | |
| | X-axis (mm) | Y-axis (mm) | | X-axis (mm) | Y-axis (mm) |
| A | +196 (4.98) | +500 (12.70) | j | +251 (6.38) | -314 (7.98) |
| B | +314 (7.98) | +435 (11.05) | j | +133 (3.38) | -379 (9.63) |
| C | +413 (10.49) | +343 (8.71) | k | +000 (0.00) | -402 (10.21) |
| D | +485 (12.32) | +230 (5.84) | m | -133 (3.38) | -379 (9.63) |
| E | +527 (13.39) | +101 (2.57) | n | -251 (6.38) | -314 (7.98) |
| F | +536 (13.61) | -030 (0.76) | p | -341 (8.66) | -213 (5.41) |
| G | +511 (12.98) | -164 (4.17) | q | -392 (9.96) | -088 (2.24) |
| H | +454 (11.53) | -287 (7.29) | r | -399 (10.13) | +046 (1.17) |
| J | +368 (9.35) | -391 (9.93) | s | -362 (9.19) | +175 (4.45) |
| K | +259 (6.58) | -470 (11.94) | t | -285 (7.24) | +283 (7.19) |
| L | +134 (3.40) | -519 (13.18) | u | -173 (4.39) | +363 (9.22) |
| M | +000 (0.00) | -537 (13.64) | v | +000 (0.00) | +338 (8.59) |
| N | -134 (3.40) | -519 (13.18) | w | +147 (3.73) | +223 (5.66) |
| P | -259 (6.58) | -470 (11.94) | x | +237 (6.02) | +122 (3.10) |
| R | -368 (9.35) | -391 (9.93) | y | +267 (6.78) | -010 (0.25) |
| S | -454 (11.53) | -287 (7.29) | z | +228 (5.79) | -139 (3.53) |
| T | -511 (12.98) | -164 (4.17) | AA | +131 (3.33) | -233 (5.92) |
| U | -536 (13.61) | -030 (0.76) | BB | +000 (0.00) | -267 (6.78) |
| V | -527 (13.39) | +101 (2.57) | CC | -131 (3.33) | -233 (5.92) |
| W | -485 (12.32) | +230 (5.84) | DD | -228 (5.79) | -139 (3.53) |
| X | -413 (10.49) | +343 (8.71) | EE | -267 (6.78) | -010 (0.25) |
| Y | -314 (7.98) | +435 (11.05) | FF | -237 (6.02) | +122 (3.10) |
| Z | -196 (4.98) | +500 (12.70) | GG | -147 (3.73) | +223 (5.66) |
| a | -068 (1.73) | +454 (11.53) | HH | +000 (0.00) | +200 (5.08) |
| b | +068 (1.73) | +454 (11.53) | JJ | +105 (2.67) | +094 (2.39) |
| c | +173 (4.39) | +363 (9.22) | KK | +135 (3.43) | -041 (1.04) |
| d | +285 (7.24) | +283 (7.19) | LL | +000 (0.00) | -132 (3.35) |
| e | +362 (9.19) | +175 (4.45) | MM | -135 (3.43) | -041 (1.04) |
| i | +399 (10.13) | -046 (1.17) | NN | -105 (2.67) | +094 (2.39) |
| g | +392 (9.96) | -088 (2.24) | PP | +000 (0.00) | +000 (0.00) |
| h | +341 (8.66) | -213 (5.41) | -- | -- | -- |

| Shell size | Arrangement no. | Number of contacts | Size contacts | Service rating | Contact location | Supersedes |
|------------|-----------------|--------------------|---------------|----------------|------------------|------------|
| 25 | -61 | 61 | 20 | I | All | MS20057-61 |

SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)

| Country | Jurisdiction & Control List |
|---------|-----------------------------|
| FR | Not Listed |

PN: 8D525X61SBL

| | | | |
|----------------|-------------------------------------|--------------------------------|---|
| A | 17-10-2016 | First Release | |
| ISS | DATE | Latest modification - by | MOD N° |
| Designed By: | | Date: | CUSTOMER DRAWING |
| TITLE | | Composite Plug 8D series | |
| SCALE | | General linear Tolerances: ±-- | NPRDS / PROJECT 859 |
| SOURIAU | | WWW.SOURIAU.COM | |
| | | | This document is the property of SOURIAU it must not be reproduced or communicated without permission |
| FORMAT | SOURIAU DRG N° 8D525X61SBL-C | | SHEET 2/2 |