



PRODUCT DESCRIPTION

At 6.4 W/m-K thermal conductivity, Tflex™ CR607 is at the forefront of thermal performance for a two-part, cure in place dispensable gap filler. This dispensable gap filler minimizes stress on components during assembly while providing the reliability of a traditional thermal pad. Tflex™ CR607 has been designed for reliability, intended to pass stringent vertical shock and vibrate requirements of the automotive industry.

The 1:1 mix is dispensable through a wide variety of dispensing equipment. It is an A+B putty material that cures in place after dispensing and mixing to perfectly fill the gap. The experts at Laird can help design the system that is right for you.

Tflex™ CR607 is a soft, compliant, high thermal conductivity dispensable gap filler providing the lowest thermal resistance and highest reliability available.

FEATURES AND BENEFITS

- Thermal Conductivity 6.4W/mK
- Dispensable and Compliant
- Easily reworkable
- Ideal for large gaps
- Meets ROHS and REACH requirements

APPLICATIONS

- Telecom base stations
- Graphic chips
- Microprocessors
- High-power automotive electronic controls

MAIN PROPERTIES

TYPICAL PROPERTIES	VALUE	TEST METHOD
Composition	Two-part ceramic filled dispensable silicone gap filler	
Color	Part A: Blue Part B:White	Visual
Flow rate (75cc taper tip, 0.125" orifice, at 90psi)	70 g/min	Laird Method
Pot life	1 hour minimum	Laird Method
Mix ratio	1:1	
Shelf Life	6 months	Laird Method
Cure conditions	24 hours at 25°C	Laird Method
PROPERTIES AFTER CURING		
Thermal Conductivity	6.4 W/mK	Hot Disk
Density	3.43 g/cc	Helium Pycnometer
Hardness (30sec)	70 Shore 00	ASTM D2240
Outgassing TML (weight)	0.11 %	ASTM E595

Americas: +1.866.928.8181

Europe: +49.8031.2460.0

Asia: +86.755.2714.1166

www.laird.com

THR-DS-Tflex™ CR607_210720

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All information is subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2013 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.

PROPERTIES AFTER CURING	CONTINUED	
TYPICAL PROPERTY	VALUE	TEST METHOD
Minimum Bond Line Thickness	150 µm	Laird Method
Operating Temperature Range	-55°C to 200°C	
Thermal Resistance at 1mm, 50°C, 345kPa	2.15 °C·cm ² /W	ASTM D5470 (Modified)
Dielectric Breakdown Voltage at 2mm	6 kV AC	ASTM D149
UL Flammability Rating	V-0 (pending)	UL
Volume Resistivity	2.5 x 10 ¹⁴ ohm·cm	ISO 14309

PACKAGING

TYPE	FILL VOLUME	FILL WEIGHT
50cc side-by-side cartridge (2x25cc)	48 cc	160 g
200cc side-by-side cartridge (2x100cc)	215 cc	730 g
400cc side-by-side cartridge (2x200cc)	394 cc	1340 g
1-gallon pail x2	4070 cc	14kg x2
5-gallons pail x2	5820 cc	20kg x2

SAMPLING

TYPE	FILL VOLUME	FILL WEIGHT
50cc side-by-side cartridge (2x25cc)	48cc	160 g

THR-DS-Tflex™ CR607_210720

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All information is subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user. Laird Technologies makes no warranties as to the fitness, merchantability, suitability or non-infringement of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies products are sold pursuant to the Laird Technologies' Terms and Conditions of sale in effect from time to time, a copy of which will be furnished upon request. © Copyright 2013 Laird Technologies, Inc. All Rights Reserved. Laird, Laird Technologies, the Laird Technologies Logo, and other marks are trademarks or registered trademarks of Laird Technologies, Inc. or an affiliate company thereof. Other product or service names may be the property of third parties. Nothing herein provides a license under any Laird Technologies or any third party intellectual property rights.