






SFSA240GV2AK4TO-C-6B-226-STD

SFSA240GV2AK4TO-I-6B-226-STD

SFSA240GU2AK4TO-C-6B-226-STD

SFSA480GU2AK2TO-C-8C-226-STD

SFSA480GU2AK2TO-I-8C-226-STD



Type	SATA: SlimSATA	SATA: SlimSATA	SATA: mSATA	SATA: mSATA	SATA: mSATA
Product Family	X-75	X-75	X-75	X-75	X-75
Flash Type	3D TLC	3D TLC	3D TLC	3D TLC	3D TLC
Density	240 GB	240 GB	240 GB	480 GB	480 GB
Temp. Grade	0 to 70°C	-40 to 85°C	0 to 70°C	0 to 70°C	-40 to 85°C
Status	in Production	in Production	in Production	in Production	in Production
For new design	Yes	Yes	Yes	Yes	Yes
Rel Cost	1	1	1	1	1
Online Availability					
Endurance Rnd.	2	2	2	2	2
Endurance Seq.	2	2	2	2	2
Perf. Seq. RD [MB/s]	565	565	565	565	565
Perf. Seq. WR [MB/s]	285	285	285	490	490
Perf. Rnd. RD [IOPS]	69300	69300	69300	73700	73700

	SFSA240GV2AK4TO-C-6B-226-STD	SFSA240GV2AK4TO-I-6B-226-STD	SFSA240GU2AK4TO-C-6B-226-STD	SFSA480GU2AK2TO-C-8C-226-STD	SFSA480GU2AK2TO-I-8C-226-STD
Perf. Rnd. WR [IOPS]	67800	67800	67800	70500	70500