-	E G T	П	C	J	0	œ	A		_
4	R 22.6 Max + U U U U U U U U U U U U U U U U U U U					YOUT SHOWN AS EXAMPLE			4
	Keyin	g Shown as example							
	CHARACTERISTICSStandard : Based on MIL-DTL-38999 Series III	Connector dimension Dim Nominal							
	-Shell Material: Aluminium-Shell Plating: Nickel-Insulator: Thermoplastic-Contacts: Copper Alloy	A 34.9±0.3 B 19.07+0.1/-0.15 R 32.5Max S 31.8±0.4 W 2.2+0.9/-0.1 VV THREAD M15x1-6g			due to a use the Specifications	not be liable for any non-confo of the Products which does no s issued by either of the Parties ional recommendation, technic	t comply with or by a third party		
N	-Seals & Grommet : Silicon Elastomer -Contact Plating : Gold over copper Alloy 0.8µm minimum					Country Ju FR	risdiction & Control List Not Listed		2
	-Durability : 500 Mating cycles -Delivered without Souriau contacts				F	N: 8D711F02SCL			
	-Temperature Range : -65°C to +200°C -Salt Spray : 48 hours			A 30-09-20	016 First Release			_	
_	-Mass : 18.78 g ± 10%			ISS DATE Designed By:	Latest modification	· · · · · · · · · · · · · · · · · · ·	CUSTOMER DRAWING	MOD N°	
				TITLE		Aluminium Recept	acle 8D series		
_	BASIC SERIES: 8D 7 - 11 F 02 S SHELL TYPE : Jam nut Receptacle Image: Second	C L Delivered W/O	Contacta	SCALE		General linear Tolerances: ±	NPRDS / PROJECT 859		
	CONTACT TYPE : Standard Crimp Contact			SOURIA	U WWW	.SOURIAU.COM	This document is the pro SOURIAU it must not be reprodu		
	SHELL SIZE : 11	CONTACT TYPE : SOCKET(500	Matings)	FORMAT			communicated without p		
	PLATING : F = Nickel		JI:11-02	A3		SOURIAU DRG N 8D711F02SCL-(1/2	
L	H G F	E	D)	С	В	A		

Г	D I	m		>			
4	Contact Layout		Panel cutout JAM NUT RECEPTACLE (TYPE 7)	4			
ω	(Insert arrangement 11-2) Contact position Contact location ID X-axis Y-axis (mm) (mm) (mm) A +.095 (2.41) +.000 (.00) B 095 (2.41) +.000 (.00) Shell Arrangement Number of contacts Size Service rating Contact size no. contacts contacts rating location 11 -2 2 16 I All		Dim Nominal B 19.59+0/-0.25 ØC 20.96+0.25/-0	3			
			SOURIAU shall not be liable for any non-conformity or damage due to a use of the Products which does not comply with the Specifications issued by either of the Parties or by a third party (professional recommendation, technical notice.)				
2			Country Jurisdiction & Control List FR Not Listed PN: 8D711F02SCL	2			
			A30-09-2016First ReleaseISSDATELatest modification - by	MOD N°			
		Designed By: Date: CUSTOMER DRAWING TITLE Aluminium Receptacle 8D series					
_			SCALE General linear NPRDS / PROJECT NA Tolerances: 859 SOURIAU WWW.SOURIAU.COM This document is the proceed of the proced of the proceed of the proceed of the proceed of the pr	duced or			
			FORMAT SOURIAU DRG N° A3 8D711F02SCL-C	SHEET 2/2			
	H G	F	D C B A	l.			