


F161YR475M050V

F161, Film, Metallized Polyester Stacked, Automotive Grade, 4.7 uF, 20%, 30 VAC, 50 VDC, 85°C, 5045, 6.5mm



Note: '()' correspond to the letters used in the product bulletin

Click here for the 3D model.

Dimensions		
Chip Size	5045	
L	12.7mm +/-0.2mm	
W	11.5mm +/-0.2mm	
Т	6.5mm +/-0.2mm	
F	0.5mm NOM	

Packaging Specifications	
Packaging	T&R
Packaging Quantity	600

General Information		
Series	F161	
Dielectric	Metallized Polyester Stacked	
Style	SMD Chip	
Features	Automotive Grade	
RoHS	Yes	
Qualifications	AEC-Q200	
AEC-Q200	Yes	
Shelf Life	104 Weeks	
MSL	3	

Specifications	
Capacitance	4.7 uF
Capacitance Tolerance	20%
Voltage AC	30 VAC
Voltage DC	50 VDC
Temperature Range	-55/+125°C
Rated Temperature	85°C
Dissipation Factor	0.8% 1kHz, 1.5% 10kHz
Insulation Resistance	85 MOhms
Max dV/dt	8 V/us

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.