

Model No.: PLS-P830987


Rev: 1

Product Line: Peerless


Last Update: 2017-03-03 09:00:02

Product Description

This 3 inch 8 ohm member of the PLS family sets a high standard, for compact full range drivers intended for applications such as television soundbars and compact music systems. Design features in this family include a damped plastic basket with venting under the spider to aid cooling of the motor, a neodymium magnet motor with copper cap to lower coil inductance, providing low distortion at low frequencies and extended high frequency response. A black anodized aluminium cone is employed on the driver, along with a black anodized aluminium dust cap coupled directly to the voice coil. Additionally, the cones come equipped with special-designed large roll rubber surrounds, which allow for a dynamic linear response to high excursion input signals.



Mechanical Drawing



Specifications

DC Resistance	Revc	Ohms	6.15	5.0%	Energy Bandwidth Product	EBP	(1/Qes)*fs	
Minimum Impedance	Zmin	Ohms	6.43	7.5%	Moving Mass	Mms	g	2.5
Voice Coil Inductance	Le	mH	0.05		Suspension Compliance	Cms	um/N	882.7
Resonant Frequency	Fs	Hz	107.97	15%	Effective Cone diameter	D	cm	6.05
Mechanical Q Factor	Qms		6.19		Effective Piston Area	Sd	cm^2	28.8
Electrical Q Factor	Qes	1.14			Effective Volume	Vas	L	1.03
Total Q Factor	Qts		0.97		Motor Force Factor	BL	Tm	3
Ratio Fs/Qts	F	Fs/Qts	111.89		Motor Efficiency Factor	β	(T*M^2)/Ohms	1.5
Half Space Sensitivity @2.83V	db@2.83V/1M	dB	83.56	+/- 1.0db	Voice coil former Material	VCfm		ASV
Half Space Sensitivity @1W/1M	db@1W/1M	dB	82.6	+/- 1.0db	Voice coil inner diameter	VCd	mm	25.73
Gap Height	Gh	mm	4		Rated Noise Power	P	W	25
Maximum Linear Excursion	Xmax	mm	2.1		Test Spectrum Bandwidth		100Hz - 20kHz	
Ferrofluid Type	FF				Driver Size	Inch	3 in	
Driver Mass	Kg	0.22						

Frequency and Impedance Response

