



カラー & キー位置 (4,6極) COLOR & KEY POSITION (4, 6 CIRCUIT)

極性キー
POLARIZATION KEY




204523**00
ナチュラル(白)
NATURAL (WHITE)


極性キー
POLARIZATION KEY




204523**03
黄
YELLOW



204523**01
黒
BLACK



204523**04
青
BLUE



204523**02
赤
RED

3 適用製品及び各種仕様書 APPLICABLE PRODUCTS AND VARIOUS SPECIFICATIONS

梱包仕様書 PACKAGING SPECIFICATION	製品番号 PART NUMBER	仕様書番号 SPECIFICATION NUMBER	
	2045230*0*	2045239200SPK PS 200	
適用端子 APPLICABLE TERMINAL	製品番号 PART NUMBER	めっきタイプ PLATING TYPE	電線サイズ WIRE SIZE(AWG)
	5054311000	TIN	#26-30
適用嵌合相手 MATE WITH	TIN PLATING VERTICAL FOR POTTING		
シリーズ番号 SERIES NO.	207760**** (4-6 CIRCUIT)		
製品仕様書 PRODUCT SPECIFICATION	2045230001-PS PS 000		
コネクタ取扱説明書 APPLICATION SPECIFICATION	AS-505432-001 PS 001		

4 204523**0* オーダー番号一覧 ORDER NO. LIST

NOT COMPLIANT			COMPLIANT		LOW HALOGEN
青 BLUE	黄 YELLOW	赤 RED	黒 BLACK	ナチュラル(白) NATURAL (WHITE)	HOUSING COLOR
2045230604	2045230603	2045230602	2045230601	2045230600	6
2045230404	2045230403	2045230402	2045230401	2045230400	4
オーダー番号 ORDER NO.					極数 CIRCUIT SIZE
梱包形態: ポリ袋 PACKAGING: POLYBAG PACKAGE					

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		CURRENT REV DESC: RELEASED		molex	
DIMENSION UNITS mm	SCALE NTS	GENERAL TOLERANCES (UNLESS SPECIFIED)			
ANGULAR TOL ± 3.0°		4 PLACES ± 0.2		PRODUCT CUSTOMER DRAWING	
3 PLACES ± 0.2		2 PLACES ± 0.2		DOCUMENT NUMBER	
1 PLACE ± 0.2		0 PLACES ± 0.2		2045230001-SD	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIRD ANGLE PROJECTION	DRAWING A3-SIZE	SERIES 204523	MATERIAL NUMBER SEE CHART
				CUSTOMER GENERAL	DOC TYPE PSD
				DOC PART 000	
				REVISION A	
				SHEET NUMBER 2 OF 2	