

UNITRONIC® BUS CAN FD P

For CAN bus systems; continuous flex applications; 120 Ω

LAPP KABEL STUÏTGART UNITRONIC® BUS CAN FD P



UNITRONIC® BUS CAN FD P is designed to the CAN open and ISO11898 standard. It is well suited for high-speed motion control and feedback loop applications, providing high reliability and efficient use of network bandwidth.

Recommended applications

Motion control systems; assembly, welding, and material handling machines; single cable wiring of multi-input sensor blocks; smart sensors; pneumatic valves; barcode readers; drives and operator interfaces

Rate table

Distance (m)	AWG	Max. rate
0 - 40	22	1 Mbps @ 40 m
40 - 300	22, 20	50 kbps @ 100 m
300 - 600	20	100 kbps @ 500 m
600 - 1000	19	50 kbps @ 1 km

Cable attributes page 648

	OIL	OR-04		FLAME	FR-02
	MOTION	CF-02*		MECH.	MP-05

Construction

Conductors: finely stranded bare copper

Insulation: polyethylene

Shielding: tinned copper braid shield

Jacket: halogen-free polyurethane; violet

Application advantage

- Designed for continuous flex applications
- Signal integrity in stationary motion applications
- Flame retardant
- Oil-resistant jacket
- Flexible for ease of routing

Approvals



Complete the installation



EPIC® DATA connectors page 186

Technical data

	Minimum bend radius:	15 x cable diameter		Nominal capacitance:	18 pF/ft
	Temperature range:	-40°C to +80°C - for installation: - for continuous flexing: -30°C to +70°C		Color code:	DIN 47100: chart 8, page 682 - pair 1: white & brown - pair 2: green & yellow
	Nominal voltage:	250V (not for power applications)		Approvals:	UL: CMX Canada: c(UL) CMX Additional: *UL Verified ID A522492: Continuous Flex Test Method Verified
	Characteristic impedance:	120 Ω ± 15Ω			

Part Nnber	Conductor description	Nominal outer diameter		Copper weight	Approx. weight	SKINTOP® MS-SC PG thread
		in	mm	lbs/mft	lbs/mft	
2170272	24 AWG / 1pr	0.252	6.4	16	27	53112210
2170273	24 AWG / 2pr	0.331	8.4	22	44	53112220
2170275	22 AWG / 1pr	0.268	6.8	22	40	53112210

Part Nnber	Conductor description	Nominal outer diameter		Copper weight	Approx. weight	SKINTOP® MS-SC PG thread
		in	mm	lbs/mft	lbs/mft	
2170276	22 AWG / 2pr	0.378	9.6	35	59	53112230
2170278	20 AWG / 1pr	0.315	8.0	28	50	53112220
2170279	20 AWG / 2pr	0.426	10.8	40	67	53112230

Recommended SKINTOP® assumes minimal OD variance. Additional configurations are available; please see our SKINTOP® section. If not otherwise specified, all values relating to the product are nominal values. Photographs are not to scale and are not true representations of the products in question.