



SS Stainless Steel

3 Type

- A** With plastic knob, without lock nut
- AK** With plastic knob, with lock nut
- AN** With stainless steel knob, without lock nut
- AKN** With stainless steel knob, with lock nut

Specification



- Threaded body
 - Steel, blackened finish —
 - Plunger pin hardened
 - Stainless steel **NI**
 - European Standard No. 1.4305 (AISI 303)
 - Plunger pin chemically nickel plated
- Knob (Type A / AK)
 - Plastic
 - Technopolymer (Polyamide PA)
 - Temperature resistant up to 230 °F (110 °C)
 - Black, matte finish
 - Not removable
- Knob (Type AN / AKN)
 - Stainless steel
 - European Standard No. 1.4305 (AISI 303)
 - Not removable
- Inch size lock nut
 - Steel, blackened finish
 - ANSI/ASME B18.2.2
 - 18-8 Stainless steel (A2)
- Metric size lock nut
 - Steel, blackened finish
 - DIN 439 B / ISO 8675
 - Stainless steel (A2)
 - DIN 439 B / ISO 8675
- RoHS compliant

Information

GN 617.1 indexing plungers with lock-out are used for applications where the plunger pin needs to stay in its retracted position. To achieve this, the knob is rotated by 90 degrees after being retracted. A notch keeps the plunger in the retracted position.

The indexing plungers completely made of stainless steel parts are a good choice for use in corrosion free environments.

see also...

- *List of Indexing Plunger Types*
- *Mounting Blocks GN 412.1*
- *Locating Bushings GN 412.2*
- *Spacer Bushings GN 609.5 (to Limit the Thread Length)*
- *Thin Hexagon Nuts GN 909 / GN 909.5 → page QVX*

How to order (Inch, steel, with plastic knob)	1 Pin diameter d_1
1 2 3 GN617.1-5-3/8X24-A	2 Thread d_2
	3 Type

How to order (Inch, stainless steel, with plastic knob)	1 Pin diameter d_1
1 2 3 4 GN617.1-6-1/2X13-AK-NI	2 Thread d_2
	3 Type
	4 Material

How to order (Metric, stainless steel, with stainless steel knob)	1 Pin diameter d_1
1 2 3 4 GN617.1-8-M16X1.5-AKN-NI	2 Thread d_2
	3 Type
	4 Material

Inch table

Dimensions in: inches - *millimeters*

1 d ₁ Pin -0.001 Bore +0.001	2 d ₂ Thread	d ₃	e	l ₁ ≈	l ₂	l ₃	l ₄	l ₅ min.	A/F	Spring load ≈			
										Steel		Stainless steel	
										Initial	End	Initial	End
.20 5	3/8 x 24	.83 21	.54 13.8	2.01 51	.20 5	.67 17	.20 5	.59 15	.47 12	1.57 lbf 7 N	3.82 lbf 17 N	1.35 lbf 6 N	3.37 lbf 15 N
.24 6	1/2 x 13	.98 25	.64 16.2	2.40 61	.24 6	.79 20	.24 6	.67 17	.55 14	2.02 lbf 9 N	5.40 lbf 24 N	1.80 lbf 8 N	4.72 lbf 21 N
.31 8	5/8 x 11	1.22 31	.86 21.9	2.97 75.5	.28 7	1.02 26	.31 8	.83 21	.75 19	2.47 lbf 11 N	6.74 lbf 30 N	2.02 lbf 9 N	5.85 lbf 26 N

Metric table

Dimensions in: millimeters - *inches*

1 d ₁ Pin -0.02 Bore H7	2 d ₂ Thread	d ₃	e	l ₁ ≈	l ₂	l ₃	l ₄	l ₅ min.	A/F	Spring load ≈			
										Steel		Stainless steel	
										Initial	End	Initial	End
5 .20	M 10 x 1	21 .83	13.8 .54	51 2.01	5 .20	17 .67	5 .20	15 .59	12 .47	7 N 1.57 lbf	17 N 3.82 lbf	6 N 1.35 lbf	15 N 3.37 lbf
6 .24	M 12 x 1.5	25 .98	16.2 .64	61 2.40	6 .24	20 .79	6 .24	17 .67	14 .55	9 N 2.02 lbf	24 N 5.40 lbf	8 N 1.80 lbf	21 N 4.72 lbf
8 .31	M 16 x 1.5	31 1.22	21.9 .86	75.5 2.97	7 .28	26 1.02	8 .31	23 .91	19 .75	11 N 2.47 lbf	30 N 6.74 lbf	9 N 2.02 lbf	26 N 5.85 lbf
10 .39	M 20 x 1.5	31 1.22	25.4 1.00	91 3.58	10 .39	33 1.30	10 .39	30 1.18	22 .87	19 N 4.27 lbf	45 N 10.12 lbf	17 N 3.82 lbf	40 N 8.99 lbf

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9

