


| NO. | MASSE / DIMENSION |
|-----|-------------------|
| A   | 30.8              |
| B   | 14.6              |
| C   | 28                |
| D   | 23.05             |
| E   | 4                 |
| F   | 70                |
| H   | 31.7              |
| I   | 34.8              |

| NO. | BESCHREIBUNG / DESCRIPTION              |
|-----|-----------------------------------------|
| 1   | ISOLIERKÖRPER STIFT / INSULATOR PIN     |
| 3   | DICHTKÖRPER / GROMMET                   |
| 5   | KONTAKTSTIFT/ CONTACT PIN               |
| 8   | DOSENGEHÄUSE / SHELL                    |
| 16  | ENDGEHÄUSE GESCHIRMT / ENDBELL SHIELDED |



Note: Due to an automatic nomenclature system, numbers generated may not be sequential.  
 Specification and Dimensions subject to change  
 Drawings illustrate normal insulator positioning

|                                |                                               |
|--------------------------------|-----------------------------------------------|
| <b>Material Specification:</b> |                                               |
| Shell Material:                | Aluminium alloy                               |
| Shell Plating:                 | Olive drab chromate over cadmium (conductive) |
| Insulator Material:            | CR-Elastomere                                 |
| Contact Material:              | Copper alloy                                  |
| Contact Plating:               | Hard silver                                   |

all dimensions are in mm  
 Dimensions without tolerance indications are general tolerances in acc. with DIN7168m  
 drawing for CUSTOMER



description CA3101E18-1P-B-15  
 Cable connecting plug shielded  
 Shielded with endbell for shielded braids & heat shrinkable boots  
 AWG Crimp / Pin / Layout: 18-1