



Click [here](#) for the 3D model.

### Dimensions

|      |                 |
|------|-----------------|
| L    | 160mm NOM       |
| W    | 70mm NOM        |
| H    | 60mm NOM        |
| Lead | Screw Terminals |

### Packaging Specifications

|                    |           |
|--------------------|-----------|
| Packaging          | Tray, Box |
| Packaging Quantity | 12        |
| Component Weight   | 1200 g    |

### General Information

|               |                                      |
|---------------|--------------------------------------|
| Series        | LF                                   |
| Style         | Metal Box                            |
| Description   | Metal Box                            |
| Phase         | Three-phase                          |
| RoHS          | With Exemptions                      |
| SCIP Number   | 10661cea-adfc-45e6-be80-e6b4fd31a87d |
| Notes         | DC Available.                        |
| Miscellaneous | 30 K Self-Temperature Rise Max.      |
| Lead          | Screw Terminals                      |
| Terminal Type | Screw                                |

### Specifications

|                   |  |
|-------------------|--|
| Voltage AC        | 250 VAC  |
| Voltage           | 1500 VAC Withstanding Voltage 1 Min. Line to Ground    |
| Rated Current     | 30 A (AC/DC)   |
| Rated Temperature | 55°C   |
| Temperature Range | -20/+55°C  |
| Leakage Current   | 1 mA MAX (250 V 60 Hz)                                 |
| Resistance        | 300 MOhms MIN Insulation 500 VDC 1 Min. Line To Ground |