

Product Search Data Sheet

Note: This datasheet may be out of date. Please download the latest datasheet of GRT188C80J226ME13# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRT188C80J226ME13%23

### "#" indicates a package specification code.



< List of part numbers with package codes > GRT188C80J226ME13D
GRT188C80J226ME13J


GRT188C80J226ME13J

# Applications

Unsuitable	Please be sure to read and comply with	
Applications	these "Precautions for use."	
	Automotive infotainment/comfort	
	equipment,Industrial Equipment,Medical	
	equipment [GHTF A/B/C] except for	
	implant equipment	
	Please refer to Our Website and	
Specific	specifications, etc. for information about	
Applications	the performance, functions, quality,	
	management, and safety required for	
	the above applications, and use	
	Products after confirming the	
	performance and reliability of the actual	
	Product.	

## Appearance & Shape







.

Derating1



## References

Packaging	Specifications	Standard Packing Quantity	
D	φ180mm Reel Paper Tape	4000	
J	φ330mm Reel Paper Tape	10000	

Mass (typ.)	
1 piece	9.1mg

1 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.





# GRT188C80J226ME13J

Note: This datasheet may be out of date. Please download the latest datasheet of GRT188C80J226ME13# from the official website of Murata Manufacturing Co., Ltd.

http://www.murata.com/en-us/products/productdetail?partno=GRT188C80J226ME13%23

#### "#" indicates a package specification code.



# Specifications

Length	1.6±0.2mm
Width	0.8±0.2mm
Thickness	0.8±0.2mm
Capacitance	22µF ±20%
Distance between external terminals g	0.6mm min.
External terminal size e	0.2 to 0.55mm
Operating Temperature Range	-55℃ to 105℃
Rated Voltage	6.3Vdc
Size code in inch(mm)	0603 (1608M)
Capacitance change rate	±22.0%
Temperature characteristics (complied standard)	X6S(EIA)
Temperature range of temperature characteristics	-55℃ to 105℃

2 of 2

#### Attention

1. This datasheet is downloaded from the website of Murata Manufacturing Co., Ltd. Therefore, it's specifications are subject to change or our products in it may be discontinued

without advance notice. Please check with our sales representatives or product engineers before ordering.

2. This datasheet has only typical specifications because there is no space for detailed specifications.

Therefore, please review our product specifications or consult the approval sheet for product specifications before ordering.

