

### product type designation

product description

### KEY-PLUG W740 iFeatures

Swap medium for activating iFeatures for SCALANCE W in Client Mode and for simple device replacement in the event of a fault

KEY-PLUG W740, Removable data storage medium for enabling of iFeatures for SCALANCE W in client mode, permits simple device replacement in event of fault and the recording of configuration data; or configuration and application data, For all SCALANCE W devices with plug slot.



suitability for use

Activation iPCF Client Mode, iPCF MC Client Mode, iPRP Client Mode

### ambient conditions

ambient temperature

- during operation
- during storage
- during transport

-40 ... +75 °C  
-40 ... +80 °C  
-40 ... +80 °C

relative humidity

- at 25 °C / without condensation / during operation / maximum

95 %

protection class IP

IP20

### design, dimensions and weights

width

24.3 mm

height

17 mm

depth

8.1 mm

net weight

5 g

design of the removable storage

- C-PLUG
- KEY-PLUG

No  
Yes

### product features, product functions, product components / general

storage capacity

256 Mibyte

### standards, specifications, approvals

reference code

- according to IEC 81346-2:2019

CFA

### further information / internet-Links

Internet-Link

- to website: TIA Selection Tool
- to web page: selection aid TIA Selection Tool
- to the website: IWLAN
- to website: Industrial communication
- to website: Industry Mall
- to website: Information and Download Center
- to website: Selection guide for cables and connectors
- to website: Image database
- to website: CAX-Download-Manager
- to website: Industry Online Support

<http://www.siemens.com/tia-selection-tool>  
<http://www.siemens.com/snst>  
<http://www.siemens.com/iwlan>  
<http://www.siemens.com/simatic-net>  
<https://mall.industry.siemens.com>  
<http://www.siemens.com/industry/infocenter>  
<https://sie.ag/2QdLxcP>  
<http://automation.siemens.com/bilddb>  
<http://www.siemens.com/cax>  
<https://support.industry.siemens.com>

last modified:

5/20/2021

